

The Red Hat newlib C Library

Full Configuration

libc 1.12.0
January 2004

Steve Chamberlain
Roland Pesch
Red Hat Support
Jeff Johnston

sac@cygnus.com, pesch@cygnus.com, jjohnstn@redhat.com *The Red Hat newlib C Library*
Copyright © 1992, 1993, 1994-2004 Red Hat Inc.

'libc' includes software developed by the University of California, Berkeley and its contributors.

'libc' includes software developed by Martin Jackson, Graham Haley and Steve Chamberlain of Tadpole Technology and released to Cygnus.

'libc' uses floating-point conversion software developed at AT&T, which includes this copyright information:

The author of this software is David M. Gay.

Copyright (c) 1991 by AT&T.

Permission to use, copy, modify, and distribute this software for any purpose without fee is hereby granted, provided that this entire notice is included in all copies of any software which is or includes a copy or modification of this software and in all copies of the supporting documentation for such software.

THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR AT&T MAKES ANY REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, subject to the terms of the GNU General Public License, which includes the provision that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions.

1 Standard Utility Functions ('stdlib.h')

This chapter groups utility functions useful in a variety of programs. The corresponding declarations are in the header file 'stdlib.h'.

1.1 abort—abnormal termination of a program

Synopsis

```
#include <stdlib.h>
void abort(void);
```

Description

Use `abort` to signal that your program has detected a condition it cannot deal with. Normally, `abort` ends your program's execution.

Before terminating your program, `abort` raises the exception `SIGABRT` (using `'raise(SIGABRT)'`). If you have used `signal` to register an exception handler for this condition, that handler has the opportunity to retain control, thereby avoiding program termination.

In this implementation, `abort` does not perform any stream- or file-related cleanup (the host environment may do so; if not, you can arrange for your program to do its own cleanup with a `SIGABRT` exception handler).

Returns

`abort` does not return to its caller.

Portability

ANSI C requires `abort`.

Supporting OS subroutines required: `_exit` and optionally, `write`.

1.2 abs—integer absolute value (magnitude)

Synopsis

```
#include <stdlib.h>
int abs(int i);
```

Description

`abs` returns $|x|$, the absolute value of i (also called the magnitude of i). That is, if i is negative, the result is the opposite of i , but if i is nonnegative the result is i .

The similar function `labs` uses and returns `long` rather than `int` values.

Returns

The result is a nonnegative integer.

Portability

`abs` is ANSI.

No supporting OS subroutines are required.

1.3 `assert`—Macro for Debugging Diagnostics

Synopsis

```
#include <assert.h>
void assert(int expression);
```

Description

Use this macro to embed debuggging diagnostic statements in your programs. The argument *expression* should be an expression which evaluates to true (nonzero) when your program is working as you intended.

When *expression* evaluates to false (zero), `assert` calls `abort`, after first printing a message showing what failed and where:

```
Assertion failed: expression, file filename, line lineno
```

The macro is defined to permit you to turn off all uses of `assert` at compile time by defining `NDEBUG` as a preprocessor variable. If you do this, the `assert` macro expands to

```
(void(0))
```

Returns

`assert` does not return a value.

Portability

The `assert` macro is required by ANSI, as is the behavior when `NDEBUG` is defined.

Supporting OS subroutines required (only if enabled): `close`, `fstat`, `getpid`, `isatty`, `kill`, `lseek`, `read`, `sbrk`, `write`.

1.4 atexit—request execution of functions at program exit

Synopsis

```
#include <stdlib.h>
int atexit (void (*function)(void));
```

Description

You can use `atexit` to enroll functions in a list of functions that will be called when your program terminates normally. The argument is a pointer to a user-defined function (which must not require arguments and must not return a result).

The functions are kept in a LIFO stack; that is, the last function enrolled by `atexit` will be the first to execute when your program exits.

There is no built-in limit to the number of functions you can enroll in this list; however, after every group of 32 functions is enrolled, `atexit` will call `malloc` to get space for the next part of the list. The initial list of 32 functions is statically allocated, so you can always count on at least that many slots available.

Returns

`atexit` returns 0 if it succeeds in enrolling your function, -1 if it fails (possible only if no space was available for `malloc` to extend the list of functions).

Portability

`atexit` is required by the ANSI standard, which also specifies that implementations must support enrolling at least 32 functions.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

1.5 atof, atoff—string to double or float

Synopsis

```
#include <stdlib.h>
double atof(const char *s);
float atoff(const char *s);
```

Description

`atof` converts the initial portion of a string to a `double`. `atoff` converts the initial portion of a string to a `float`.

The functions parse the character string `s`, locating a substring which can be converted to a floating-point value. The substring must match the format:

```
[+|-]digits[.][digits][[e|E][+|-]digits]
```

The substring converted is the longest initial fragment of `s` that has the expected format, beginning with the first non-whitespace character. The substring is empty if `str` is empty, consists entirely of whitespace, or if the first non-whitespace character is something other than `+`, `-`, `.`, or a digit.

`atof(s)` is implemented as `strtod(s, NULL)`. `atoff(s)` is implemented as `strtof(s, NULL)`.

Returns

`atof` returns the converted substring value, if any, as a `double`; or `0.0`, if no conversion could be performed. If the correct value is out of the range of representable values, plus or minus `HUGE_VAL` is returned, and `ERANGE` is stored in `errno`. If the correct value would cause underflow, `0.0` is returned and `ERANGE` is stored in `errno`.

`atoff` obeys the same rules as `atof`, except that it returns a `float`.

Portability

`atof` is ANSI C. `atof`, `atoi`, and `atol` are subsumed by `strod` and `strol`, but are used extensively in existing code. These functions are less reliable, but may be faster if the argument is verified to be in a valid range.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

1.6 atoi, atol—string to integer

Synopsis

```
#include <stdlib.h>
int atoi(const char *s);
long atol(const char *s);
int _atoi_r(struct _reent *ptr, const char *s);
long _atol_r(struct _reent *ptr, const char *s);
```

Description

`atoi` converts the initial portion of a string to an `int`. `atol` converts the initial portion of a string to a `long`.

`atoi(s)` is implemented as `(int)strtol(s, NULL, 10)`. `atol(s)` is implemented as `strtol(s, NULL, 10)`.

`_atoi_r` and `_atol_r` are reentrant versions of `atoi` and `atol` respectively, passing the reentrancy struct pointer.

Returns

The functions return the converted value, if any. If no conversion was made, 0 is returned.

Portability

`atoi`, `atol` are ANSI.

No supporting OS subroutines are required.

1.7 `atoll`—convert a string to a long long integer

Synopsis

```
#include <stdlib.h>
long long atoll(const char *str);
long long _atoll_r(struct _reent *ptr, const char *str);
```

Description

The function `atoll` converts the initial portion of the string pointed to by `*str` to a type `long long`. A call to `atoll(str)` in this implementation is equivalent to `strtoll(str, (char **)NULL, 10)` including behavior on error.

The alternate function `_atoll_r` is a reentrant version. The extra argument `reent` is a pointer to a reentrancy structure.

Returns

The converted value.

Portability

`atoll` is ISO 9899 (C99) and POSIX 1003.1-2001 compatible.

No supporting OS subroutines are required.

1.8 calloc—allocate space for arrays

Synopsis

```
#include <stdlib.h>
void *calloc(size_t n, size_t s);
void *calloc_r(void *reent, size_t <n>, <size_t> s);
```

Description

Use `calloc` to request a block of memory sufficient to hold an array of n elements, each of which has size s .

The memory allocated by `calloc` comes out of the same memory pool used by `malloc`, but the memory block is initialized to all zero bytes. (To avoid the overhead of initializing the space, use `malloc` instead.)

The alternate function `_calloc_r` is reentrant. The extra argument `reent` is a pointer to a reentrancy structure.

Returns

If successful, a pointer to the newly allocated space.

If unsuccessful, `NULL`.

Portability

`calloc` is ANSI.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

1.9 `div`—divide two integers

Synopsis

```
#include <stdlib.h>
div_t div(int n, int d);
```

Description

Divide n/d , returning quotient and remainder as two integers in a structure `div_t`.

Returns

The result is represented with the structure

```
typedef struct
{
    int quot;
    int rem;
} div_t;
```

where the `quot` field represents the quotient, and `rem` the remainder. For nonzero d , if ' $r = \text{div}(n, d)$;' then n equals ' $r.\text{rem} + d*r.\text{quot}$ '.

To divide `long` rather than `int` values, use the similar function `ldiv`.

Portability

`div` is ANSI.

No supporting OS subroutines are required.

1.10 `ecvt`, `ecvtf`, `fcvt`, `fcvtf`—double or float to string

Synopsis

```
#include <stdlib.h>

char *ecvt(double val, int chars, int *decpt, int *sgn);
char *ecvtf(float val, int chars, int *decpt, int *sgn);

char *fcvt(double val, int decimals,
            int *decpt, int *sgn);
char *fcvtf(float val, int decimals,
            int *decpt, int *sgn);
```

Description

`ecvt` and `fcvt` produce (null-terminated) strings of digits representing the double number `val`. `ecvtf` and `fcvtf` produce the corresponding character representations of float numbers.

(The `stdlib` functions `ecvtbuf` and `fcvtbuf` are reentrant versions of `ecvt` and `fcvt`.)

The only difference between `ecvt` and `fcvt` is the interpretation of the second argument (`chars` or `decimals`). For `ecvt`, the second argument `chars` specifies the total number of characters to write (which is also the number of significant digits in the formatted string, since these two functions write only digits). For `fcvt`, the second argument `decimals` specifies the number of characters to write after the decimal point; all digits for the integer part of `val` are always included.

Since `ecvt` and `fcvt` write only digits in the output string, they record the location of the decimal point in `*decpt`, and the sign of the number in `*sgn`. After formatting a number, `*decpt` contains the number of digits to the left of the decimal point. `*sgn` contains 0 if the number is positive, and 1 if it is negative.

Returns

All four functions return a pointer to the new string containing a character representation of `val`.

Portability

None of these functions are ANSI C.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

1.11 `gcvvt`, `gcvtf`—format double or float as string

Synopsis

```
#include <stdlib.h>
```

```
char *gcvt(double val, int precision, char *buf);
```

```
char *gcvtf(float val, int precision, char *buf);
```

Description

`gcvt` writes a fully formatted number as a null-terminated string in the buffer `*buf`. `gcvtf` produces corresponding character representations of `float` numbers.

`gcvt` uses the same rules as the `printf` format `%.precisiong`—only negative values are signed (with `'-'`), and either exponential or ordinary decimal-fraction format is chosen depending on the number of significant digits (specified by `precision`).

Returns

The result is a pointer to the formatted representation of `val` (the same as the argument `buf`).

Portability

Neither function is ANSI C.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

1.12 `ecvtbuf`, `fcvtbuf`—double or float to string

Synopsis

```
#include <stdio.h>

char *ecvtbuf(double val, int chars, int *decpt,
              int *sgn, char *buf);

char *fcvtbuf(double val, int decimals, int *decpt,
              int *sgn, char *buf);
```

Description

`ecvtbuf` and `fcvtbuf` produce (null-terminated) strings of digits representing the double number *val*.

The only difference between `ecvtbuf` and `fcvtbuf` is the interpretation of the second argument (*chars* or *decimals*). For `ecvtbuf`, the second argument *chars* specifies the total number of characters to write (which is also the number of significant digits in the formatted string, since these two functions write only digits). For `fcvtbuf`, the second argument *decimals* specifies the number of characters to write after the decimal point; all digits for the integer part of *val* are always included.

Since `ecvtbuf` and `fcvtbuf` write only digits in the output string, they record the location of the decimal point in **decpt*, and the sign of the number in **sgn*. After formatting a number, **decpt* contains the number of digits to the left of the decimal point. **sgn* contains 0 if the number is positive, and 1 if it is negative. For both functions, you supply a pointer *buf* to an area of memory to hold the converted string.

Returns

Both functions return a pointer to *buf*, the string containing a character representation of *val*.

Portability

Neither function is ANSI C.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

1.13 `__env_lock`, `__env_unlock`—lock environ variable

Synopsis

```
#include "envlock.h"
void __env_lock (struct _reent *reent);
void __env_unlock (struct _reent *reent);
```

Description

The `setenv` family of routines call these functions when they need to modify the environ variable. The version of these routines supplied in the library does not do anything. If multiple threads of execution can call `setenv`, or if `setenv` can be called reentrantly, then you need to define your own versions of these functions in order to safely lock the memory pool during a call. If you do not, the memory pool may become corrupted.

A call to `setenv` may call `__env_lock` recursively; that is, the sequence of calls may go `__env_lock`, `__env_lock`, `__env_unlock`, `__env_unlock`. Any implementation of these routines must be careful to avoid causing a thread to wait for a lock that it already holds.

1.14 `exit`—end program execution

Synopsis

```
#include <stdlib.h>
void exit(int code);
```

Description

Use `exit` to return control from a program to the host operating environment. Use the argument *code* to pass an exit status to the operating environment: two particular values, `EXIT_SUCCESS` and `EXIT_FAILURE`, are defined in 'stdlib.h' to indicate success or failure in a portable fashion.

`exit` does two kinds of cleanup before ending execution of your program. First, it calls all application-defined cleanup functions you have enrolled with `atexit`. Second, files and streams are cleaned up: any pending output is delivered to the host system, each open file or stream is closed, and files created by `tmpfile` are deleted.

Returns

`exit` does not return to its caller.

Portability

ANSI C requires `exit`, and specifies that `EXIT_SUCCESS` and `EXIT_FAILURE` must be defined. Supporting OS subroutines required: `_exit`.

1.15 `getenv`—look up environment variable

Synopsis

```
#include <stdlib.h>
char *getenv(const char *name);
```

Description

`getenv` searches the list of environment variable names and values (using the global pointer “`char **environ`”) for a variable whose name matches the string at *name*. If a variable name matches, `getenv` returns a pointer to the associated value.

Returns

A pointer to the (string) value of the environment variable, or `NULL` if there is no such environment variable.

Portability

`getenv` is ANSI, but the rules for properly forming names of environment variables vary from one system to another.

`getenv` requires a global pointer `environ`.

1.16 labs—long integer absolute value

Synopsis

```
#include <stdlib.h>
long labs(long i);
```

Description

`labs` returns $|x|$, the absolute value of i (also called the magnitude of i). That is, if i is negative, the result is the opposite of i , but if i is nonnegative the result is i .

The similar function `abs` uses and returns `int` rather than `long` values.

Returns

The result is a nonnegative long integer.

Portability

`labs` is ANSI.

No supporting OS subroutine calls are required.

1.17 ldiv—divide two long integers

Synopsis

```
#include <stdlib.h>
ldiv_t ldiv(long n, long d);
```

Description

Divide n/d , returning quotient and remainder as two long integers in a structure `ldiv_t`.

Returns

The result is represented with the structure

```
typedef struct
{
    long quot;
    long rem;
} ldiv_t;
```

where the `quot` field represents the quotient, and `rem` the remainder. For nonzero d , if '`r = ldiv(n,d)`;' then n equals '`r.rem + d*r.quot`'.

To divide `int` rather than `long` values, use the similar function `div`.

Portability

`ldiv` is ANSI.

No supporting OS subroutines are required.

1.18 labs—compute the absolute value of a long long integer.

Synopsis

```
#include <stdlib.h>
long long labs(long long j);
```

Description

The `labs` function computes the absolute value of the long long integer argument *j* (also called the magnitude of *j*).

The similar function `labs` uses and returns `long` rather than `long long` values.

Returns

A nonnegative long long integer.

Portability

`labs` is ISO 9899 (C99) compatible.

No supporting OS subroutines are required.

1.19 `lldiv`—divide two long long integers

Synopsis

```
#include <stdlib.h>
lldiv_t lldiv(long long n, long long d);
```

Description

Divide n/d , returning quotient and remainder as two long long integers in a structure `lldiv_t`.

Returns

The result is represented with the structure

```
typedef struct
{
    long long quot;
    long long rem;
} lldiv_t;
```

where the `quot` field represents the quotient, and `rem` the remainder. For nonzero d , if ' $r = \text{ldiv}(n, d)$;' then n equals ' $r.\text{rem} + d*r.\text{quot}$ '.

To divide `long` rather than `long long` values, use the similar function `ldiv`.

Portability

`lldiv` is ISO 9899 (C99) compatible.

No supporting OS subroutines are required.

1.20 malloc, realloc, free—manage memory

Synopsis

```
#include <stdlib.h>
void *malloc(size_t nbytes);
void *realloc(void *aptr, size_t nbytes);
void free(void *aptr);

void *memalign(size_t align, size_t nbytes);

size_t malloc_usable_size(void *aptr);

void *_malloc_r(void *reent, size_t nbytes);
void *_realloc_r(void *reent,
                void *aptr, size_t nbytes);
void _free_r(void *reent, void *aptr);

void *_memalign_r(void *reent,
                 size_t align, size_t nbytes);

size_t _malloc_usable_size_r(void *reent, void *aptr);
```

Description

These functions manage a pool of system memory.

Use `malloc` to request allocation of an object with at least *nbytes* bytes of storage available. If the space is available, `malloc` returns a pointer to a newly allocated block as its result.

If you already have a block of storage allocated by `malloc`, but you no longer need all the space allocated to it, you can make it smaller by calling `realloc` with both the object pointer and the new desired size as arguments. `realloc` guarantees that the contents of the smaller object match the beginning of the original object.

Similarly, if you need more space for an object, use `realloc` to request the larger size; again, `realloc` guarantees that the beginning of the new, larger object matches the contents of the original object.

When you no longer need an object originally allocated by `malloc` or `realloc` (or the related function `calloc`), return it to the memory storage pool by calling `free` with the address of the object as the argument. You can also use `realloc` for this purpose by calling it with 0 as the *nbytes* argument.

The `memalign` function returns a block of size *nbytes* aligned to a *align* boundary. The *align* argument must be a power of two.

The `malloc_usable_size` function takes a pointer to a block allocated by `malloc`. It returns the amount of space that is available in the block. This may or may not be more than the size requested from `malloc`, due to alignment or minimum size constraints.

The alternate functions `_malloc_r`, `_realloc_r`, `_free_r`, `_memalign_r`, and `_malloc_usable_size_r` are reentrant versions. The extra argument *reent* is a pointer to a reentrancy structure.

If you have multiple threads of execution which may call any of these routines, or if any of these routines may be called reentrantly, then you must provide implementations of the `__malloc_lock` and `__malloc_unlock` functions for your system. See the documentation for those functions.

These functions operate by calling the function `_sbrk_r` or `sbrk`, which allocates space. You may need to provide one of these functions for your system. `_sbrk_r` is called with a positive value to allocate more space, and with a negative value to release previously allocated space if it is no longer required. See Section 11.1 [Stubs], page 211.

Returns

`malloc` returns a pointer to the newly allocated space, if successful; otherwise it returns `NULL`. If your application needs to generate empty objects, you may use `malloc(0)` for this purpose.

`realloc` returns a pointer to the new block of memory, or `NULL` if a new block could not be allocated. `NULL` is also the result when you use `'realloc(aptr,0)'` (which has the same effect as `'free(aptr)'`). You should always check the result of `realloc`; successful reallocation is not guaranteed even when you request a smaller object.

`free` does not return a result.

`memalign` returns a pointer to the newly allocated space.

`malloc_usable_size` returns the usable size.

Portability

`malloc`, `realloc`, and `free` are specified by the ANSI C standard, but other conforming implementations of `malloc` may behave differently when `nbytes` is zero.

`memalign` is part of SVR4.

`malloc_usable_size` is not portable.

Supporting OS subroutines required: `sbrk`.

1.21 mallinfo, malloc_stats, mallopt—malloc support

Synopsis

```
#include <malloc.h>
struct mallinfo mallinfo(void);
void malloc_stats(void);
int mallopt(int parameter, value);

struct mallinfo _mallinfo_r(void *reent);
void _malloc_stats_r(void *reent);
int _mallopt_r(void *reent, int parameter, value);
```

Description

mallinfo returns a structure describing the current state of memory allocation. The structure is defined in `malloc.h`. The following fields are defined: **arena** is the total amount of space in the heap; **ordblks** is the number of chunks which are not in use; **uordblks** is the total amount of space allocated by **malloc**; **fordblks** is the total amount of space not in use; **keepcost** is the size of the top most memory block.

malloc_stats print some statistics about memory allocation on standard error.

mallopt takes a parameter and a value. The parameters are defined in `malloc.h`, and may be one of the following: **M_TRIM_THRESHOLD** sets the maximum amount of unused space in the top most block before releasing it back to the system in **free** (the space is released by calling **_sbrk_r** with a negative argument); **M_TOP_PAD** is the amount of padding to allocate whenever **_sbrk_r** is called to allocate more space.

The alternate functions **_mallinfo_r**, **_malloc_stats_r**, and **_mallopt_r** are reentrant versions. The extra argument *reent* is a pointer to a reentrancy structure.

Returns

mallinfo returns a `mallinfo` structure. The structure is defined in `malloc.h`.

malloc_stats does not return a result.

mallopt returns zero if the parameter could not be set, or non-zero if it could be set.

Portability

mallinfo and **mallopt** are provided by SVR4, but **mallopt** takes different parameters on different systems. **malloc_stats** is not portable.

1.22 `__malloc_lock`, `__malloc_unlock`—lock malloc pool

Synopsis

```
#include <malloc.h>
void __malloc_lock (struct _reent *reent);
void __malloc_unlock (struct _reent *reent);
```

Description

The `malloc` family of routines call these functions when they need to lock the memory pool. The version of these routines supplied in the library does not do anything. If multiple threads of execution can call `malloc`, or if `malloc` can be called reentrantly, then you need to define your own versions of these functions in order to safely lock the memory pool during a call. If you do not, the memory pool may become corrupted.

A call to `malloc` may call `__malloc_lock` recursively; that is, the sequence of calls may go `__malloc_lock`, `__malloc_lock`, `__malloc_unlock`, `__malloc_unlock`. Any implementation of these routines must be careful to avoid causing a thread to wait for a lock that it already holds.

1.23 mblen—minimal multibyte length function

Synopsis

```
#include <stdlib.h>
int mblen(const char *s, size_t n);
```

Description

When `MB_CAPABLE` is not defined, this is a minimal ANSI-conforming implementation of `mblen`. In this case, the only “multi-byte character sequences” recognized are single bytes, and thus 1 is returned unless `s` is the null pointer or has a length of 0 or is the empty string. When `MB_CAPABLE` is defined, this routine calls `_mbtowc_r` to perform the conversion, passing a state variable to allow state dependent decoding. The result is based on the locale setting which may be restricted to a defined set of locales.

Returns

This implementation of `mblen` returns 0 if `s` is `NULL` or the empty string; it returns 1 if not `MB_CAPABLE` or the character is a single-byte character; it returns -1 if the multi-byte character is invalid; otherwise it returns the number of bytes in the multibyte character.

Portability

`mblen` is required in the ANSI C standard. However, the precise effects vary with the locale. `mblen` requires no supporting OS subroutines.

1.24 `mbstowcs`—minimal multibyte string to wide char converter

Synopsis

```
#include <stdlib.h>
int mbstowcs(wchar_t *pwc, const char *s, size_t n);
```

Description

When `MB_CAPABLE` is not defined, this is a minimal ANSI-conforming implementation of `mbstowcs`. In this case, the only “multi-byte character sequences” recognized are single bytes, and they are “converted” to wide-char versions simply by byte extension.

When `MB_CAPABLE` is defined, this routine calls `_mbstowcs_r` to perform the conversion, passing a state variable to allow state dependent decoding. The result is based on the locale setting which may be restricted to a defined set of locales.

Returns

This implementation of `mbstowcs` returns 0 if `s` is `NULL` or is the empty string; it returns -1 if `MB_CAPABLE` and one of the multi-byte characters is invalid or incomplete; otherwise it returns the minimum of: `n` or the number of multi-byte characters in `s` plus 1 (to compensate for the nul character). If the return value is -1, the state of the `pwc` string is indeterminate. If the input has a length of 0, the output string will be modified to contain a `wchar_t` nul terminator.

Portability

`mbstowcs` is required in the ANSI C standard. However, the precise effects vary with the locale.

`mbstowcs` requires no supporting OS subroutines.

1.25 mbtowc—minimal multibyte to wide char converter

Synopsis

```
#include <stdlib.h>
int mbtowc(wchar_t *pwc, const char *s, size_t n);
```

Description

When `MB_CAPABLE` is not defined, this is a minimal ANSI-conforming implementation of `mbtowc`. In this case, only “multi-byte character sequences” recognized are single bytes, and they are “converted” to themselves. Each call to `mbtowc` copies one character from `*s` to `*pwc`, unless `s` is a null pointer. The argument `n` is ignored.

When `MB_CAPABLE` is defined, this routine calls `_mbtowc_r` to perform the conversion, passing a state variable to allow state dependent decoding. The result is based on the locale setting which may be restricted to a defined set of locales.

Returns

This implementation of `mbtowc` returns 0 if `s` is `NULL` or is the empty string; it returns 1 if not `MB_CAPABLE` or the character is a single-byte character; it returns -1 if `n` is 0 or the multi-byte character is invalid; otherwise it returns the number of bytes in the multibyte character. If the return value is -1, no changes are made to the `pwc` output string. If the input is the empty string, a `wchar_t` nul is placed in the output string and 0 is returned. If the input has a length of 0, no changes are made to the `pwc` output string.

Portability

`mbtowc` is required in the ANSI C standard. However, the precise effects vary with the locale.

`mbtowc` requires no supporting OS subroutines.

1.26 rand, srand—pseudo-random numbers

Synopsis

```
#include <stdlib.h>
int rand(void);
void srand(unsigned int seed);
int rand_r(unsigned int *seed);
```

Description

rand returns a different integer each time it is called; each integer is chosen by an algorithm designed to be unpredictable, so that you can use **rand** when you require a random number. The algorithm depends on a static variable called the “random seed”; starting with a given value of the random seed always produces the same sequence of numbers in successive calls to **rand**.

You can set the random seed using **srand**; it does nothing beyond storing its argument in the static variable used by **rand**. You can exploit this to make the pseudo-random sequence less predictable, if you wish, by using some other unpredictable value (often the least significant parts of a time-varying value) as the random seed before beginning a sequence of calls to **rand**; or, if you wish to ensure (for example, while debugging) that successive runs of your program use the same “random” numbers, you can use **srand** to set the same random seed at the outset.

Returns

rand returns the next pseudo-random integer in sequence; it is a number between 0 and `RAND_MAX` (inclusive).

srand does not return a result.

Portability

rand is required by ANSI, but the algorithm for pseudo-random number generation is not specified; therefore, even if you use the same random seed, you cannot expect the same sequence of results on two different systems.

rand requires no supporting OS subroutines.

1.27 rand48, drand48, erand48, lrand48, nrand48, mrand48, jrand48, srand48, seed48, lcong48 —pseudo random number generators and initialization routines

Synopsis

```
#include <stdlib.h>
double drand48(void);
double erand48(unsigned short xseed[3]);
long lrand48(void);
long nrand48(unsigned short xseed[3]);
long mrand48(void);
long jrand48(unsigned short xseed[3]);
void srand48(long seed);
unsigned short *seed48(unsigned short xseed[3]);
void lcong48(unsigned short p[7]);
```

Description

The **rand48** family of functions generates pseudo-random numbers using a linear congruential algorithm working on integers 48 bits in size. The particular formula employed is $r(n+1) = (a * r(n) + c) \bmod m$ where the default values are for the multiplicand $a = 0xfdece66d = 25214903917$ and the addend $c = 0xb = 11$. The modulo is always fixed at $m = 2^{**} 48$. $r(n)$ is called the seed of the random number generator.

For all the six generator routines described next, the first computational step is to perform a single iteration of the algorithm.

drand48 and **erand48** return values of type `double`. The full 48 bits of $r(n+1)$ are loaded into the mantissa of the returned value, with the exponent set such that the values produced lie in the interval $[0.0, 1.0]$.

lrand48 and **nrand48** return values of type `long` in the range $[0, 2^{**}31-1]$. The high-order (31) bits of $r(n+1)$ are loaded into the lower bits of the returned value, with the topmost (sign) bit set to zero.

mrnd48 and **jrnd48** return values of type `long` in the range $[-2^{**}31, 2^{**}31-1]$. The high-order (32) bits of $r(n+1)$ are loaded into the returned value.

drand48, **lrand48**, and **mrnd48** use an internal buffer to store $r(n)$. For these functions the initial value of $r(0) = 0x1234abcd330e = 20017429951246$.

On the other hand, **erand48**, **nrand48**, and **jrnd48** use a user-supplied buffer to store the seed $r(n)$, which consists of an array of 3 shorts, where the zeroth member holds the least significant bits.

All functions share the same multiplicand and addend.

srand48 is used to initialize the internal buffer $r(n)$ of **drand48**, **lrand48**, and **mrnd48** such that the 32 bits of the seed value are copied into the upper 32 bits of $r(n)$, with the lower 16 bits of $r(n)$ arbitrarily being set to `0x330e`. Additionally, the constant multiplicand and addend of the algorithm are reset to the default values given above.

seed48 also initializes the internal buffer $r(n)$ of **drand48**, **lrand48**, and **mrnd48**, but here all 48 bits of the seed can be specified in an array of 3 shorts, where the zeroth member specifies the lowest bits. Again, the constant multiplicand and addend of the algorithm are reset to the default values given above. **seed48** returns a pointer to an array of 3 shorts

which contains the old seed. This array is statically allocated, thus its contents are lost after each new call to `seed48`.

Finally, `lcong48` allows full control over the multiplicand and addend used in `drand48`, `erand48`, `lrand48`, `rand48`, `mrnd48`, and `jrand48`, and the seed used in `drand48`, `lrand48`, and `mrnd48`. An array of 7 shorts is passed as parameter; the first three shorts are used to initialize the seed; the second three are used to initialize the multiplicand; and the last short is used to initialize the addend. It is thus not possible to use values greater than `0xffff` as the addend.

Note that all three methods of seeding the random number generator always also set the multiplicand and addend for any of the six generator calls.

For a more powerful random number generator, see `random`.

Portability

SUS requires these functions.

No supporting OS subroutines are required.

1.28 strtod, strtodf—string to double or float

Synopsis

```
#include <stdlib.h>
double strtod(const char *str, char **tail);
float strtodf(const char *str, char **tail);

double _strtod_r(void *reent,
                 const char *str, char **tail);
```

Description

The function `strtod` parses the character string `str`, producing a substring which can be converted to a double value. The substring converted is the longest initial subsequence of `str`, beginning with the first non-whitespace character, that has the format:

```
[+|-]digits[.][digits][(e|E)[+|-]digits]
```

The substring contains no characters if `str` is empty, consists entirely of whitespace, or if the first non-whitespace character is something other than `+`, `-`, `.`, or a digit. If the substring is empty, no conversion is done, and the value of `str` is stored in `*tail`. Otherwise, the substring is converted, and a pointer to the final string (which will contain at least the terminating null character of `str`) is stored in `*tail`. If you want no assignment to `*tail`, pass a null pointer as `tail`. `strtodf` is identical to `strtod` except for its return type.

This implementation returns the nearest machine number to the input decimal string. Ties are broken by using the IEEE round-even rule.

The alternate function `_strtod_r` is a reentrant version. The extra argument `reent` is a pointer to a reentrancy structure.

Returns

`strtod` returns the converted substring value, if any. If no conversion could be performed, 0 is returned. If the correct value is out of the range of representable values, plus or minus `HUGE_VAL` is returned, and `ERANGE` is stored in `errno`. If the correct value would cause underflow, 0 is returned and `ERANGE` is stored in `errno`.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

1.29 strtol—string to long

Synopsis

```
#include <stdlib.h>
long strtol(const char *s, char **ptr,int base);

long _strtol_r(void *reent,
               const char *s, char **ptr,int base);
```

Description

The function `strtol` converts the string `*s` to a `long`. First, it breaks down the string into three parts: leading whitespace, which is ignored; a subject string consisting of characters resembling an integer in the radix specified by `base`; and a trailing portion consisting of zero or more unparseable characters, and always including the terminating null character. Then, it attempts to convert the subject string into a `long` and returns the result.

If the value of `base` is 0, the subject string is expected to look like a normal C integer constant: an optional sign, a possible ‘0x’ indicating a hexadecimal base, and a number. If `base` is between 2 and 36, the expected form of the subject is a sequence of letters and digits representing an integer in the radix specified by `base`, with an optional plus or minus sign. The letters a–z (or, equivalently, A–Z) are used to signify values from 10 to 35; only letters whose ascribed values are less than `base` are permitted. If `base` is 16, a leading 0x is permitted.

The subject sequence is the longest initial sequence of the input string that has the expected form, starting with the first non-whitespace character. If the string is empty or consists entirely of whitespace, or if the first non-whitespace character is not a permissible letter or digit, the subject string is empty.

If the subject string is acceptable, and the value of `base` is zero, `strtol` attempts to determine the radix from the input string. A string with a leading 0x is treated as a hexadecimal value; a string with a leading 0 and no x is treated as octal; all other strings are treated as decimal. If `base` is between 2 and 36, it is used as the conversion radix, as described above. If the subject string begins with a minus sign, the value is negated. Finally, a pointer to the first character past the converted subject string is stored in `ptr`, if `ptr` is not NULL.

If the subject string is empty (or not in acceptable form), no conversion is performed and the value of `s` is stored in `ptr` (if `ptr` is not NULL).

The alternate function `_strtol_r` is a reentrant version. The extra argument `reent` is a pointer to a reentrancy structure.

Returns

`strtol` returns the converted value, if any. If no conversion was made, 0 is returned.

`strtol` returns `LONG_MAX` or `LONG_MIN` if the magnitude of the converted value is too large, and sets `errno` to `ERANGE`.

Portability

`strtol` is ANSI.

No supporting OS subroutines are required.

1.30 strtoul—string to unsigned long

Synopsis

```
#include <stdlib.h>
unsigned long strtoul(const char *s, char **ptr,
                    int base);

unsigned long _strtoul_r(void *reent, const char *s,
                      char **ptr, int base);
```

Description

The function `strtoul` converts the string `*s` to an unsigned long. First, it breaks down the string into three parts: leading whitespace, which is ignored; a subject string consisting of the digits meaningful in the radix specified by `base` (for example, 0 through 7 if the value of `base` is 8); and a trailing portion consisting of one or more unparseable characters, which always includes the terminating null character. Then, it attempts to convert the subject string into an unsigned long integer, and returns the result.

If the value of `base` is zero, the subject string is expected to look like a normal C integer constant (save that no optional sign is permitted): a possible `0x` indicating hexadecimal radix, and a number. If `base` is between 2 and 36, the expected form of the subject is a sequence of digits (which may include letters, depending on the base) representing an integer in the radix specified by `base`. The letters `a–z` (or `A–Z`) are used as digits valued from 10 to 35. If `base` is 16, a leading `0x` is permitted.

The subject sequence is the longest initial sequence of the input string that has the expected form, starting with the first non-whitespace character. If the string is empty or consists entirely of whitespace, or if the first non-whitespace character is not a permissible digit, the subject string is empty.

If the subject string is acceptable, and the value of `base` is zero, `strtoul` attempts to determine the radix from the input string. A string with a leading `0x` is treated as a hexadecimal value; a string with a leading `0` and no `x` is treated as octal; all other strings are treated as decimal. If `base` is between 2 and 36, it is used as the conversion radix, as described above. Finally, a pointer to the first character past the converted subject string is stored in `ptr`, if `ptr` is not `NULL`.

If the subject string is empty (that is, if `*s` does not start with a substring in acceptable form), no conversion is performed and the value of `s` is stored in `ptr` (if `ptr` is not `NULL`).

The alternate function `_strtoul_r` is a reentrant version. The extra argument `reent` is a pointer to a reentrancy structure.

Returns

`strtoul` returns the converted value, if any. If no conversion was made, 0 is returned.

`strtoul` returns `ULONG_MAX` if the magnitude of the converted value is too large, and sets `errno` to `ERANGE`.

Portability

`strtoul` is ANSI.

`strtoul` requires no supporting OS subroutines.

1.31 `system`—execute command string

Synopsis

```
#include <stdlib.h>
int system(char *s);

int _system_r(void *reent, char *s);
```

Description

Use `system` to pass a command string `*s` to `/bin/sh` on your system, and wait for it to finish executing.

Use “`system(NULL)`” to test whether your system has `/bin/sh` available.

The alternate function `_system_r` is a reentrant version. The extra argument `reent` is a pointer to a reentrancy structure.

Returns

`system(NULL)` returns a non-zero value if `/bin/sh` is available, and 0 if it is not.

With a command argument, the result of `system` is the exit status returned by `/bin/sh`.

Portability

ANSI C requires `system`, but leaves the nature and effects of a command processor undefined. ANSI C does, however, specify that `system(NULL)` return zero or nonzero to report on the existence of a command processor.

POSIX.2 requires `system`, and requires that it invoke a `sh`. Where `sh` is found is left unspecified.

Supporting OS subroutines required: `_exit`, `_execve`, `_fork_r`, `_wait_r`.

1.32 wcstombs—minimal wide char string to multibyte string converter

Synopsis

```
#include <stdlib.h>
int wcstombs(const char *s, wchar_t *pwc, size_t n);
```

Description

When `MB_CAPABLE` is not defined, this is a minimal ANSI-conforming implementation of `wcstombs`. In this case, all wide-characters are expected to represent single bytes and so are converted simply by casting to `char`.

When `MB_CAPABLE` is defined, this routine calls `_wcstombs_r` to perform the conversion, passing a state variable to allow state dependent decoding. The result is based on the locale setting which may be restricted to a defined set of locales.

Returns

This implementation of `wcstombs` returns 0 if `s` is `NULL` or is the empty string; it returns -1 if `MB_CAPABLE` and one of the wide-char characters does not represent a valid multi-byte character; otherwise it returns the minimum of: `n` or the number of bytes that are transferred to `s`, not including the nul terminator.

If the return value is -1, the state of the `pwc` string is indeterminate. If the input has a length of 0, the output string will be modified to contain a `wchar_t` nul terminator if `n > 0`.

Portability

`wcstombs` is required in the ANSI C standard. However, the precise effects vary with the locale.

`wcstombs` requires no supporting OS subroutines.

1.33 `wctomb`—minimal wide char to multibyte converter

Synopsis

```
#include <stdlib.h>
int wctomb(char *s, wchar_t wchar);
```

Description

When `MB_CAPABLE` is not defined, this is a minimal ANSI-conforming implementation of `wctomb`. The only “wide characters” recognized are single bytes, and they are “converted” to themselves.

When `MB_CAPABLE` is defined, this routine calls `_wctomb_r` to perform the conversion, passing a state variable to allow state dependent decoding. The result is based on the locale setting which may be restricted to a defined set of locales.

Each call to `wctomb` modifies `*s` unless `s` is a null pointer or `MB_CAPABLE` is defined and `wchar` is invalid.

Returns

This implementation of `wctomb` returns 0 if `s` is `NULL`; it returns -1 if `MB_CAPABLE` is enabled and the `wchar` is not a valid multi-byte character, it returns 1 if `MB_CAPABLE` is not defined or the `wchar` is in reality a single byte character, otherwise it returns the number of bytes in the multi-byte character.

Portability

`wctomb` is required in the ANSI C standard. However, the precise effects vary with the locale.

`wctomb` requires no supporting OS subroutines.

2 Character Type Macros and Functions (`'ctype.h'`)

This chapter groups macros (which are also available as subroutines) to classify characters into several categories (alphabetic, numeric, control characters, whitespace, and so on), or to perform simple character mappings.

The header file `'ctype.h'` defines the macros.

2.1 `isalnum`—alphanumeric character predicate

Synopsis

```
#include <ctype.h>
int isalnum(int c);
```

Description

`isalnum` is a macro which classifies ASCII integer values by table lookup. It is a predicate returning non-zero for alphabetic or numeric ASCII characters, and 0 for other arguments. It is defined for all integer values.

You can use a compiled subroutine instead of the macro definition by undefining the macro using `#undef isalnum`.

Returns

`isalnum` returns non-zero if `c` is a letter (`a-z` or `A-Z`) or a digit (`0-9`).

Portability

`isalnum` is ANSI C.

No OS subroutines are required.

2.2 isalpha—alphabetic character predicate

Synopsis

```
#include <ctype.h>
int isalpha(int c);
```

Description

`isalpha` is a macro which classifies ASCII integer values by table lookup. It is a predicate returning non-zero when `c` represents an alphabetic ASCII character, and 0 otherwise. It is defined only when `isascii(c)` is true or `c` is EOF.

You can use a compiled subroutine instead of the macro definition by undefining the macro using `#undef isalpha`.

Returns

`isalpha` returns non-zero if `c` is a letter (A–Z or a–z).

Portability

`isalpha` is ANSI C.

No supporting OS subroutines are required.

2.3 `isascii`—ASCII character predicate

Synopsis

```
#include <ctype.h>
int isascii(int c);
```

Description

`isascii` is a macro which returns non-zero when `c` is an ASCII character, and 0 otherwise. It is defined for all integer values.

You can use a compiled subroutine instead of the macro definition by undefining the macro using `#undef isascii`.

Returns

`isascii` returns non-zero if the low order byte of `c` is in the range 0 to 127 (0x00–0x7F).

Portability

`isascii` is ANSI C.

No supporting OS subroutines are required.

2.4 iscntrl—control character predicate

Synopsis

```
#include <ctype.h>
int iscntrl(int c);
```

Description

`iscntrl` is a macro which classifies ASCII integer values by table lookup. It is a predicate returning non-zero for control characters, and 0 for other characters. It is defined only when `isascii(c)` is true or `c` is EOF.

You can use a compiled subroutine instead of the macro definition by undefining the macro using `#undef iscntrl`.

Returns

`iscntrl` returns non-zero if `c` is a delete character or ordinary control character (0x7F or 0x00–0x1F).

Portability

`iscntrl` is ANSI C.

No supporting OS subroutines are required.

2.5 `isdigit`—decimal digit predicate

Synopsis

```
#include <ctype.h>
int isdigit(int c);
```

Description

`isdigit` is a macro which classifies ASCII integer values by table lookup. It is a predicate returning non-zero for decimal digits, and 0 for other characters. It is defined only when `isascii(c)` is true or `c` is EOF.

You can use a compiled subroutine instead of the macro definition by undefining the macro using `#undef isdigit`.

Returns

`isdigit` returns non-zero if `c` is a decimal digit (0–9).

Portability

`isdigit` is ANSI C.

No supporting OS subroutines are required.

2.6 islower—lower-case character predicate

Synopsis

```
#include <ctype.h>
int islower(int c);
```

Description

`islower` is a macro which classifies ASCII integer values by table lookup. It is a predicate returning non-zero for minuscules (lower-case alphabetic characters), and 0 for other characters. It is defined only when `isascii(c)` is true or `c` is EOF.

You can use a compiled subroutine instead of the macro definition by undefining the macro using `#undef islower`.

Returns

`islower` returns non-zero if `c` is a lower case letter (a-z).

Portability

`islower` is ANSI C.

No supporting OS subroutines are required.

2.7 isprint, isgraph—printable character predicates

Synopsis

```
#include <ctype.h>
int isprint(int c);
int isgraph(int c);
```

Description

`isprint` is a macro which classifies ASCII integer values by table lookup. It is a predicate returning non-zero for printable characters, and 0 for other character arguments. It is defined only when `isascii(c)` is true or `c` is EOF.

You can use a compiled subroutine instead of the macro definition by undefining either macro using `#undef isprint` or `#undef isgraph`.

Returns

`isprint` returns non-zero if `c` is a printing character, (0x20–0x7E). `isgraph` behaves identically to `isprint`, except that the space character (0x20) is excluded.

Portability

`isprint` and `isgraph` are ANSI C.

No supporting OS subroutines are required.

2.8 ispunct—punctuation character predicate

Synopsis

```
#include <ctype.h>
int ispunct(int c);
```

Description

`ispunct` is a macro which classifies ASCII integer values by table lookup. It is a predicate returning non-zero for printable punctuation characters, and 0 for other characters. It is defined only when `isascii(c)` is true or `c` is EOF.

You can use a compiled subroutine instead of the macro definition by undefining the macro using `#undef ispunct`.

Returns

`ispunct` returns non-zero if `c` is a printable punctuation character (`isgraph(c) && !isalnum(c)`).

Portability

`ispunct` is ANSI C.

No supporting OS subroutines are required.

2.9 isspace—whitespace character predicate

Synopsis

```
#include <ctype.h>
int isspace(int c);
```

Description

`isspace` is a macro which classifies ASCII integer values by table lookup. It is a predicate returning non-zero for whitespace characters, and 0 for other characters. It is defined only when `isascii(c)` is true or `c` is EOF.

You can use a compiled subroutine instead of the macro definition by undefining the macro using `#undef isspace`.

Returns

`isspace` returns non-zero if `c` is a space, tab, carriage return, new line, vertical tab, or formfeed (0x09–0x0D, 0x20).

Portability

`isspace` is ANSI C.

No supporting OS subroutines are required.

2.10 isupper—uppercase character predicate

Synopsis

```
#include <ctype.h>
int isupper(int c);
```

Description

`isupper` is a macro which classifies ASCII integer values by table lookup. It is a predicate returning non-zero for upper-case letters (A–Z), and 0 for other characters. It is defined only when `isascii(c)` is true or `c` is EOF.

You can use a compiled subroutine instead of the macro definition by undefining the macro using `#undef isupper`.

Returns

`isupper` returns non-zero if `c` is a upper case letter (A-Z).

Portability

`isupper` is ANSI C.

No supporting OS subroutines are required.

2.11 `isxdigit`—hexadecimal digit predicate

Synopsis

```
#include <ctype.h>
int isxdigit(int c);
```

Description

`isxdigit` is a macro which classifies ASCII integer values by table lookup. It is a predicate returning non-zero for hexadecimal digits, and 0 for other characters. It is defined only when `isascii(c)` is true or `c` is EOF.

You can use a compiled subroutine instead of the macro definition by undefining the macro using `#undef isxdigit`.

Returns

`isxdigit` returns non-zero if `c` is a hexadecimal digit (0–9, a–f, or A–F).

Portability

`isxdigit` is ANSI C.

No supporting OS subroutines are required.

2.12 toascii—force integers to ASCII range

Synopsis

```
#include <ctype.h>
int toascii(int c);
```

Description

toascii is a macro which coerces integers to the ASCII range (0–127) by zeroing any higher-order bits.

You can use a compiled subroutine instead of the macro definition by undefining this macro using '#undef toascii'.

Returns

toascii returns integers between 0 and 127.

Portability

toascii is not ANSI C.

No supporting OS subroutines are required.

2.13 `tolower`—translate characters to lower case

Synopsis

```
#include <ctype.h>
int tolower(int c);
int _tolower(int c);
```

Description

`tolower` is a macro which converts upper-case characters to lower case, leaving all other characters unchanged. It is only defined when `c` is an integer in the range EOF to 255.

You can use a compiled subroutine instead of the macro definition by undefining this macro using `#undef tolower`.

`_tolower` performs the same conversion as `tolower`, but should only be used when `c` is known to be an uppercase character (A–Z).

Returns

`tolower` returns the lower-case equivalent of `c` when it is a character between A and Z, and `c` otherwise.

`_tolower` returns the lower-case equivalent of `c` when it is a character between A and Z. If `c` is not one of these characters, the behaviour of `_tolower` is undefined.

Portability

`tolower` is ANSI C. `_tolower` is not recommended for portable programs.

No supporting OS subroutines are required.

2.14 toupper—translate characters to upper case

Synopsis

```
#include <ctype.h>
int toupper(int c);
int _toupper(int c);
```

Description

`toupper` is a macro which converts lower-case characters to upper case, leaving all other characters unchanged. It is only defined when `c` is an integer in the range EOF to 255.

You can use a compiled subroutine instead of the macro definition by undefining this macro using `#undef toupper`.

`_toupper` performs the same conversion as `toupper`, but should only be used when `c` is known to be a lowercase character (a-z).

Returns

`toupper` returns the upper-case equivalent of `c` when it is a character between `a` and `z`, and `c` otherwise.

`_toupper` returns the upper-case equivalent of `c` when it is a character between `a` and `z`. If `c` is not one of these characters, the behaviour of `_toupper` is undefined.

Portability

`toupper` is ANSI C. `_toupper` is not recommended for portable programs.

No supporting OS subroutines are required.

2.15 iswalnum—alpha-numeric wide-character test

Synopsis

```
#include <wctype.h>
int iswalnum(wint_t c);
```

Description

`iswalnum` is a function which classifies wide-character values that are alpha-numeric.

Returns

`iswalnum` returns non-zero if `c` is a alpha-numeric wide-character.

Portability

`iswalnum` is C99.

No supporting OS subroutines are required.

2.16 iswalpha—alphabetic wide-character test

Synopsis

```
#include <wctype.h>
int iswalpha(wint_t c);
```

Description

`iswalpha` is a function which classifies wide-character values that are alphabetic.

Returns

`iswalpha` returns non-zero if `c` is an alphabetic wide-character.

Portability

`iswalpha` is C99.

No supporting OS subroutines are required.

2.17 iswcntrl—wide-character cntrl test

Synopsis

```
#include <wctype.h>
int iswcntrl(wint_t c);
```

Description

`iswcntrl` is a function which classifies wide-character values that are categorized as a control character.

Returns

`iswcntrl` returns non-zero if `c` is a control wide-character.

Portability

`iswcntrl` is C99.

No supporting OS subroutines are required.

2.18 iswdigit—decimal digit wide-character test

Synopsis

```
#include <wctype.h>
int iswdigit(wint_t c);
```

Description

iswdigit is a function which classifies wide-character values that are decimal digits.

Returns

iswdigit returns non-zero if *c* is a decimal digit wide-character.

Portability

iswdigit is C99.

No supporting OS subroutines are required.

2.19 iswgraph—graphic wide-character test

Synopsis

```
#include <wctype.h>
int iswgraph(wint_t c);
```

Description

`iswgraph` is a function which classifies wide-character values that are graphic.

Returns

`iswgraph` returns non-zero if `c` is a graphic wide-character.

Portability

`iswgraph` is C99.

No supporting OS subroutines are required.

2.20 iswlower—lower-case wide-character test

Synopsis

```
#include <wctype.h>
int iswlower(wint_t c);
```

Description

`iswlower` is a function which classifies wide-character values that have an upper-case translation.

Returns

`iswlower` returns non-zero if `c` is a lower-case wide-character.

Portability

`iswlower` is C99.

No supporting OS subroutines are required.

2.21 iswprint—printable wide-character test

Synopsis

```
#include <wctype.h>
int iswprint(wint_t c);
```

Description

`iswprint` is a function which classifies wide-character values that are printable.

Returns

`iswprint` returns non-zero if `c` is a printable wide-character.

Portability

`iswprint` is C99.

No supporting OS subroutines are required.

2.22 iswpunct—punctuation wide-character test

Synopsis

```
#include <wctype.h>
int iswpunct(wint_t c);
```

Description

iswpunct is a function which classifies wide-character values that are punctuation.

Returns

iswpunct returns non-zero if *c* is a punctuation wide-character.

Portability

iswpunct is C99.

No supporting OS subroutines are required.

2.23 iswspace—wide-character space test

Synopsis

```
#include <wctype.h>
int iswspace(wint_t c);
```

Description

`iswspace` is a function which classifies wide-character values that are categorized as white-space.

Returns

`iswspace` returns non-zero if `c` is a white-space wide-character.

Portability

`iswspace` is C99.

No supporting OS subroutines are required.

2.24 iswupper—upper-case wide-character test

Synopsis

```
#include <wctype.h>
int iswupper(wint_t c);
```

Description

`iswupper` is a function which classifies wide-character values that have an upper-case translation.

Returns

`iswupper` returns non-zero if `c` is a upper-case wide-character.

Portability

`iswupper` is C99.

No supporting OS subroutines are required.

2.25 `iswxdigit`—hexadecimal digit wide-character test

Synopsis

```
#include <wctype.h>
int iswxdigit(wint_t c);
```

Description

`iswxdigit` is a function which classifies wide-character values that are hexadecimal digits.

Returns

`iswxdigit` returns non-zero if `c` is a hexadecimal digit wide-character.

Portability

`iswxdigit` is C99.

No supporting OS subroutines are required.

2.26 iswctype—extensible wide-character test

Synopsis

```
#include <wctype.h>
int iswctype(wint_t c, wctype_t desc);
```

Description

`iswctype` is a function which classifies wide-character values using the wide-character test specified by *desc*.

Returns

`iswctype` returns non-zero if and only if *c* matches the test specified by *desc*. If *desc* is unknown, zero is returned.

Portability

`iswctype` is C99.

No supporting OS subroutines are required.

2.27 `wctype`—get wide-character classification type

Synopsis

```
#include <wctype.h>
wctype_t wctype(const char *c);
```

Description

`wctype` is a function which takes a string `c` and gives back the appropriate `wctype_t` type value associated with the string, if one exists. The following values are guaranteed to be recognized: "alnum", "alpha", "blank", "cntrl", "digit", "graph", "lower", "print", "punct", "space", "upper", and "xdigit".

Returns

`wctype` returns 0 and sets `errno` to `EINVAL` if the given name is invalid. Otherwise, it returns a valid non-zero `wctype_t` value.

Portability

`wctype` is C99.

No supporting OS subroutines are required.

2.28 towlower—translate wide-characters to lower case

Synopsis

```
#include <wctype.h>
wint_t towlower(wint_t c);
```

Description

`towlower` is a function which converts upper-case wide-characters to lower case, leaving all other characters unchanged.

Returns

`towlower` returns the lower-case equivalent of `c` when it is a upper-case wide-character, otherwise, it returns the input character.

Portability

`towlower` is C99.

No supporting OS subroutines are required.

2.29 towupper—translate wide-characters to upper case

Synopsis

```
#include <wctype.h>
wint_t towupper(wint_t c);
```

Description

`towupper` is a function which converts lower-case wide-characters to upper case, leaving all other characters unchanged.

Returns

`towupper` returns the upper-case equivalent of `c` when it is a lower-case wide-character, otherwise, it returns the input character.

Portability

`towupper` is C99.

No supporting OS subroutines are required.

2.30 towctrans—extensible wide-character case mapping

Synopsis

```
#include <wctype.h>
wint_t towctrans(wint_t c, wctrans_t w);
```

Description

`towctrans` is a function which converts wide-characters based on a specified translation type `w`. If the translation type is invalid or cannot be applied to the current character, no change to the character is made.

Returns

`towctrans` returns the translated equivalent of `c` when it is a valid for the given translation, otherwise, it returns the input character. When the translation type is invalid, `errno` is set `EINVAL`.

Portability

`towctrans` is C99.

No supporting OS subroutines are required.

2.31 wctrans—get wide-character translation type

Synopsis

```
#include <wctype.h>
wctrans_t wctrans(const char *c);
```

Description

`wctrans` is a function which takes a string `c` and gives back the appropriate `wctrans_t` type value associated with the string, if one exists. The following values are guaranteed to be recognized: "tolower" and "toupper".

Returns

`wctrans` returns 0 and sets `errno` to `EINVAL` if the given name is invalid. Otherwise, it returns a valid non-zero `wctrans_t` value.

Portability

`wctrans` is C99.

No supporting OS subroutines are required.

3 Input and Output ('stdio.h')

This chapter comprises functions to manage files or other input/output streams. Among these functions are subroutines to generate or scan strings according to specifications from a format string.

The underlying facilities for input and output depend on the host system, but these functions provide a uniform interface.

The corresponding declarations are in 'stdio.h'.

The reentrant versions of these functions use macros

```
_stdin_r(reent)  
_stdout_r(reent)  
_stderr_r(reent)
```

instead of the globals `stdin`, `stdout`, and `stderr`. The argument `<[reent]>` is a pointer to a reentrancy structure.

3.1 clearerr—clear file or stream error indicator

Synopsis

```
#include <stdio.h>
void clearerr(FILE *fp);
```

Description

The `stdio` functions maintain an error indicator with each file pointer *fp*, to record whether any read or write errors have occurred on the associated file or stream. Similarly, it maintains an end-of-file indicator to record whether there is no more data in the file.

Use `clearerr` to reset both of these indicators.

See `ferror` and `feof` to query the two indicators.

Returns

`clearerr` does not return a result.

Portability

ANSI C requires `clearerr`.

No supporting OS subroutines are required.

3.2 fclose—close a file

Synopsis

```
#include <stdio.h>
int fclose(FILE *fp);
```

Description

If the file or stream identified by *fp* is open, `fclose` closes it, after first ensuring that any pending data is written (by calling `fflush(fp)`).

Returns

`fclose` returns 0 if successful (including when *fp* is NULL or not an open file); otherwise, it returns EOF.

Portability

`fclose` is required by ANSI C.

Required OS subroutines: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.3 feof—test for end of file

Synopsis

```
#include <stdio.h>
int feof(FILE *fp);
```

Description

`feof` tests whether or not the end of the file identified by *fp* has been reached.

Returns

`feof` returns 0 if the end of file has not yet been reached; if at end of file, the result is nonzero.

Portability

`feof` is required by ANSI C.

No supporting OS subroutines are required.

3.4 `ferror`—test whether read/write error has occurred

Synopsis

```
#include <stdio.h>
int ferror(FILE *fp);
```

Description

The `stdio` functions maintain an error indicator with each file pointer *fp*, to record whether any read or write errors have occurred on the associated file or stream. Use `ferror` to query this indicator.

See `clearerr` to reset the error indicator.

Returns

`ferror` returns 0 if no errors have occurred; it returns a nonzero value otherwise.

Portability

ANSI C requires `ferror`.

No supporting OS subroutines are required.

3.5 fflush—flush buffered file output

Synopsis

```
#include <stdio.h>
int fflush(FILE *fp);
```

Description

The `stdio` output functions can buffer output before delivering it to the host system, in order to minimize the overhead of system calls.

Use `fflush` to deliver any such pending output (for the file or stream identified by *fp*) to the host system.

If *fp* is `NULL`, `fflush` delivers pending output from all open files.

Returns

`fflush` returns 0 unless it encounters a write error; in that situation, it returns `EOF`.

Portability

ANSI C requires `fflush`.

No supporting OS subroutines are required.

3.6 fgetc—get a character from a file or stream

Synopsis

```
#include <stdio.h>
int fgetc(FILE *fp);
```

Description

Use `fgetc` to get the next single character from the file or stream identified by `fp`. As a side effect, `fgetc` advances the file's current position indicator.

For a macro version of this function, see `getc`.

Returns

The next character (read as an **unsigned char**, and cast to `int`), unless there is no more data, or the host system reports a read error; in either of these situations, `fgetc` returns `EOF`.

You can distinguish the two situations that cause an `EOF` result by using the `ferror` and `feof` functions.

Portability

ANSI C requires `fgetc`.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.7 `fgetpos`—record position in a stream or file

Synopsis

```
#include <stdio.h>
int fgetpos(FILE *fp, fpos_t *pos);
int _fgetpos_r(struct _reent *ptr, FILE *fp, fpos_t *pos);
```

Description

Objects of type `FILE` can have a “position” that records how much of the file your program has already read. Many of the `stdio` functions depend on this position, and many change it as a side effect.

You can use `fgetpos` to report on the current position for a file identified by `fp`; `fgetpos` will write a value representing that position at `*pos`. Later, you can use this value with `fsetpos` to return the file to this position.

In the current implementation, `fgetpos` simply uses a character count to represent the file position; this is the same number that would be returned by `ftell`.

Returns

`fgetpos` returns 0 when successful. If `fgetpos` fails, the result is 1. Failure occurs on streams that do not support positioning; the global `errno` indicates this condition with the value `ESPIPE`.

Portability

`fgetpos` is required by the ANSI C standard, but the meaning of the value it records is not specified beyond requiring that it be acceptable as an argument to `fsetpos`. In particular, other conforming C implementations may return a different result from `ftell` than what `fgetpos` writes at `*pos`.

No supporting OS subroutines are required.

3.8 fgets—get character string from a file or stream

Synopsis

```
#include <stdio.h>
char *fgets(char *buf, int n, FILE *fp);
```

Description

Reads at most $n-1$ characters from *fp* until a newline is found. The characters including to the newline are stored in *buf*. The buffer is terminated with a 0.

Returns

fgets returns the buffer passed to it, with the data filled in. If end of file occurs with some data already accumulated, the data is returned with no other indication. If no data are read, NULL is returned instead.

Portability

fgets should replace all uses of *gets*. Note however that *fgets* returns all of the data, while *gets* removes the trailing newline (with no indication that it has done so.)

Supporting OS subroutines required: *close*, *fstat*, *isatty*, *lseek*, *read*, *sbrk*, *write*.

3.9 `fiprintf`—format output to file (integer only)

Synopsis

```
#include <stdio.h>
```

```
int fiprintf(FILE *fd, const char *format, ...);
```

Description

`fiprintf` is a restricted version of `fprintf`: it has the same arguments and behavior, save that it cannot perform any floating-point formatting—the `f`, `g`, `G`, `e`, and `F` type specifiers are not recognized.

Returns

`fiprintf` returns the number of bytes in the output string, save that the concluding `NULL` is not counted. `fiprintf` returns when the end of the format string is encountered. If an error occurs, `fiprintf` returns `EOF`.

Portability

`fiprintf` is not required by ANSI C.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.10 fopen—open a file

Synopsis

```
#include <stdio.h>
FILE *fopen(const char *file, const char *mode);

FILE *_fopen_r(void *reent,
               const char *file, const char *mode);
```

Description

`fopen` initializes the data structures needed to read or write a file. Specify the file's name as the string at *file*, and the kind of access you need to the file with the string at *mode*.

The alternate function `_fopen_r` is a reentrant version. The extra argument *reent* is a pointer to a reentrancy structure.

Three fundamental kinds of access are available: read, write, and append. **mode* must begin with one of the three characters 'r', 'w', or 'a', to select one of these:

- r** Open the file for reading; the operation will fail if the file does not exist, or if the host system does not permit you to read it.
- w** Open the file for writing *from the beginning* of the file: effectively, this always creates a new file. If the file whose name you specified already existed, its old contents are discarded.
- a** Open the file for appending data, that is writing from the end of file. When you open a file this way, all data always goes to the current end of file; you cannot change this using `fseek`.

Some host systems distinguish between “binary” and “text” files. Such systems may perform data transformations on data written to, or read from, files opened as “text”. If your system is one of these, then you can append a 'b' to any of the three modes above, to specify that you are opening the file as a binary file (the default is to open the file as a text file).

'rb', then, means “read binary”; 'wb', “write binary”; and 'ab', “append binary”.

To make C programs more portable, the 'b' is accepted on all systems, whether or not it makes a difference.

Finally, you might need to both read and write from the same file. You can also append a '+' to any of the three modes, to permit this. (If you want to append both 'b' and '+', you can do it in either order: for example, "rb+" means the same thing as "r+b" when used as a mode string.)

Use "r+" (or "rb+") to permit reading and writing anywhere in an existing file, without discarding any data; "w+" (or "wb+") to create a new file (or begin by discarding all data from an old one) that permits reading and writing anywhere in it; and "a+" (or "ab+") to permit reading anywhere in an existing file, but writing only at the end.

Returns

`fopen` returns a file pointer which you can use for other file operations, unless the file you requested could not be opened; in that situation, the result is NULL. If the reason for failure was an invalid string at *mode*, `errno` is set to EINVAL.

Portability

`fopen` is required by ANSI C.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `open`, `read`, `sbrk`, `write`.

3.11 fdopen—turn open file into a stream

Synopsis

```
#include <stdio.h>
FILE *fdopen(int fd, const char *mode);
FILE *_fdopen_r(void *reent,
                int fd, const char *mode);
```

Description

`fdopen` produces a file descriptor of type `FILE *`, from a descriptor for an already-open file (returned, for example, by the system subroutine `open` rather than by `fopen`). The *mode* argument has the same meanings as in `fopen`.

Returns

File pointer or `NULL`, as for `fopen`.

Portability

`fdopen` is ANSI.

3.12 `fputc`—write a character on a stream or file

Synopsis

```
#include <stdio.h>
int fputc(int ch, FILE *fp);
```

Description

`fputc` converts the argument *ch* from an `int` to an `unsigned char`, then writes it to the file or stream identified by *fp*.

If the file was opened with append mode (or if the stream cannot support positioning), then the new character goes at the end of the file or stream. Otherwise, the new character is written at the current value of the position indicator, and the position indicator advances by one.

For a macro version of this function, see `putc`.

Returns

If successful, `fputc` returns its argument *ch*. If an error intervenes, the result is EOF. You can use `'ferror(fp)'` to query for errors.

Portability

`fputc` is required by ANSI C.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.13 fputs—write a character string in a file or stream

Synopsis

```
#include <stdio.h>
int fputs(const char *s, FILE *fp);
```

Description

`fputs` writes the string at `s` (but without the trailing null) to the file or stream identified by `fp`.

Returns

If successful, the result is 0; otherwise, the result is EOF.

Portability

ANSI C requires `fputs`, but does not specify that the result on success must be 0; any non-negative value is permitted.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.14 fread—read array elements from a file

Synopsis

```
#include <stdio.h>
size_t fread(void *buf, size_t size, size_t count,
             FILE *fp);
```

Description

fread attempts to copy, from the file or stream identified by *fp*, *count* elements (each of size *size*) into memory, starting at *buf*. **fread** may copy fewer elements than *count* if an error, or end of file, intervenes.

fread also advances the file position indicator (if any) for *fp* by the number of *characters* actually read.

Returns

The result of **fread** is the number of elements it succeeded in reading.

Portability

ANSI C requires **fread**.

Supporting OS subroutines required: **close**, **fstat**, **isatty**, **lseek**, **read**, **sbrk**, **write**.

3.15 freopen—open a file using an existing file descriptor

Synopsis

```
#include <stdio.h>
FILE *freopen(const char *file, const char *mode,
              FILE *fp);
FILE *_freopen_r(struct _reent *ptr, const char *file,
                 const char *mode, FILE *fp);
```

Description

Use this variant of `fopen` if you wish to specify a particular file descriptor `fp` (notably `stdin`, `stdout`, or `stderr`) for the file.

If `fp` was associated with another file or stream, `freopen` closes that other file or stream (but ignores any errors while closing it).

`file` and `mode` are used just as in `fopen`.

Returns

If successful, the result is the same as the argument `fp`. If the file cannot be opened as specified, the result is `NULL`.

Portability

ANSI C requires `freopen`.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `open`, `read`, `sbrk`, `write`.

3.16 `fseek`, `fseeko`—set file position

Synopsis

```
#include <stdio.h>
int fseek(FILE *fp, long offset, int whence)
int fseeko(FILE *fp, off_t offset, int whence)
int _fseek_r(struct _reent *ptr, FILE *fp,
             long offset, int whence)
int _fseeko_r(struct _reent *ptr, FILE *fp,
              off_t offset, int whence)
```

Description

Objects of type `FILE` can have a “position” that records how much of the file your program has already read. Many of the `stdio` functions depend on this position, and many change it as a side effect.

You can use `fseek/fseeko` to set the position for the file identified by `fp`. The value of `offset` determines the new position, in one of three ways selected by the value of `whence` (defined as macros in ‘`stdio.h`’):

`SEEK_SET`—`offset` is the absolute file position (an offset from the beginning of the file) desired. `offset` must be positive.

`SEEK_CUR`—`offset` is relative to the current file position. `offset` can meaningfully be either positive or negative.

`SEEK_END`—`offset` is relative to the current end of file. `offset` can meaningfully be either positive (to increase the size of the file) or negative.

See `ftell/ftello` to determine the current file position.

Returns

`fseek/fseeko` return 0 when successful. On failure, the result is `EOF`. The reason for failure is indicated in `errno`: either `ESPIPE` (the stream identified by `fp` doesn’t support repositioning) or `EINVAL` (invalid file position).

Portability

ANSI C requires `fseek`.

`fseeko` is defined by the Single Unix specification.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.17 fsetpos—restore position of a stream or file

Synopsis

```
#include <stdio.h>
int fsetpos(FILE *fp, const fpos_t *pos);
int _fsetpos_r(struct _reent *ptr, FILE *fp, 1
               const fpos_t *pos);
```

Description

Objects of type `FILE` can have a “position” that records how much of the file your program has already read. Many of the `stdio` functions depend on this position, and many change it as a side effect.

You can use `fsetpos` to return the file identified by `fp` to a previous position `*pos` (after first recording it with `fgetpos`).

See `fseek` for a similar facility.

Returns

`fgetpos` returns 0 when successful. If `fgetpos` fails, the result is 1. The reason for failure is indicated in `errno`: either `ESPIPE` (the stream identified by `fp` doesn't support repositioning) or `EINVAL` (invalid file position).

Portability

ANSI C requires `fsetpos`, but does not specify the nature of `*pos` beyond identifying it as written by `fgetpos`.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.18 `ftell`, `ftello`—return position in a stream or file

Synopsis

```
#include <stdio.h>
long ftell(FILE *fp);
off_t ftello(FILE *fp);
long _ftell_r(struct _reent *ptr, FILE *fp);
off_t _ftello_r(struct _reent *ptr, FILE *fp);
```

Description

Objects of type `FILE` can have a “position” that records how much of the file your program has already read. Many of the `stdio` functions depend on this position, and many change it as a side effect.

The result of `ftell/ftello` is the current position for a file identified by `fp`. If you record this result, you can later use it with `fseek/fseeko` to return the file to this position. The difference between `ftell` and `ftello` is that `ftell` returns `long` and `ftello` returns `off_t`.

In the current implementation, `ftell/ftello` simply uses a character count to represent the file position; this is the same number that would be recorded by `fgetpos`.

Returns

`ftell/ftello` return the file position, if possible. If they cannot do this, they return `-1L`. Failure occurs on streams that do not support positioning; the global `errno` indicates this condition with the value `ESPIPE`.

Portability

`ftell` is required by the ANSI C standard, but the meaning of its result (when successful) is not specified beyond requiring that it be acceptable as an argument to `fseek`. In particular, other conforming C implementations may return a different result from `ftell` than what `fgetpos` records.

`ftello` is defined by the Single Unix specification.

No supporting OS subroutines are required.

3.19 fwrite—write array elements

Synopsis

```
#include <stdio.h>
size_t fwrite(const void *buf, size_t size,
              size_t count, FILE *fp);
```

Description

`fwrite` attempts to copy, starting from the memory location *buf*, *count* elements (each of size *size*) into the file or stream identified by *fp*. `fwrite` may copy fewer elements than *count* if an error intervenes.

`fwrite` also advances the file position indicator (if any) for *fp* by the number of *characters* actually written.

Returns

If `fwrite` succeeds in writing all the elements you specify, the result is the same as the argument *count*. In any event, the result is the number of complete elements that `fwrite` copied to the file.

Portability

ANSI C requires `fwrite`.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.20 `getc`—read a character (macro)

Synopsis

```
#include <stdio.h>
int getc(FILE *fp);
```

Description

`getc` is a macro, defined in `stdio.h`. You can use `getc` to get the next single character from the file or stream identified by `fp`. As a side effect, `getc` advances the file's current position indicator.

For a subroutine version of this macro, see `fgetc`.

Returns

The next character (read as an `unsigned char`, and cast to `int`), unless there is no more data, or the host system reports a read error; in either of these situations, `getc` returns `EOF`.

You can distinguish the two situations that cause an `EOF` result by using the `ferror` and `feof` functions.

Portability

ANSI C requires `getc`; it suggests, but does not require, that `getc` be implemented as a macro. The standard explicitly permits macro implementations of `getc` to use the argument more than once; therefore, in a portable program, you should not use an expression with side effects as the `getc` argument.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.21 `getchar`—read a character (macro)

Synopsis

```
#include <stdio.h>
int getchar(void);

int _getchar_r(void *reent);
```

Description

`getchar` is a macro, defined in `stdio.h`. You can use `getchar` to get the next single character from the standard input stream. As a side effect, `getchar` advances the standard input's current position indicator.

The alternate function `_getchar_r` is a reentrant version. The extra argument *reent* is a pointer to a reentrancy structure.

Returns

The next character (read as an `unsigned char`, and cast to `int`), unless there is no more data, or the host system reports a read error; in either of these situations, `getchar` returns `EOF`.

You can distinguish the two situations that cause an `EOF` result by using '`ferror(stdin)`' and '`feof(stdin)`'.

Portability

ANSI C requires `getchar`; it suggests, but does not require, that `getchar` be implemented as a macro.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.22 `gets`—get character string (obsolete, use `fgets` instead)

Synopsis

```
#include <stdio.h>

char *gets(char *buf);

char *_gets_r(void *reent, char *buf);
```

Description

Reads characters from standard input until a newline is found. The characters up to the newline are stored in *buf*. The newline is discarded, and the buffer is terminated with a 0. This is a *dangerous* function, as it has no way of checking the amount of space available in *buf*. One of the attacks used by the Internet Worm of 1988 used this to overrun a buffer allocated on the stack of the finger daemon and overwrite the return address, causing the daemon to execute code downloaded into it over the connection.

The alternate function `_gets_r` is a reentrant version. The extra argument *reent* is a pointer to a reentrancy structure.

Returns

`gets` returns the buffer passed to it, with the data filled in. If end of file occurs with some data already accumulated, the data is returned with no other indication. If end of file occurs with no data in the buffer, NULL is returned.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.23 `getw`—read a word (`int`)

Synopsis

```
#include <stdio.h>
int getw(FILE *fp);
```

Description

`getw` is a function, defined in `stdio.h`. You can use `getw` to get the next word from the file or stream identified by `fp`. As a side effect, `getw` advances the file's current position indicator.

RETURNS The next word (read as an `int`), unless there is no more data, or the host system reports a read error; in either of these situations, `getw` returns `EOF`. Since `EOF` is a valid `int`, you must use `ferror` or `feof` to distinguish these situations.

Portability

`getw` is a remnant of K&R C, it is not part of any ISO C Standard. `fread` should be used instead. In fact, this implementation of `getw` is based upon `fread`.

Supporting OS subroutines required: `fread`.

3.24 `iprintf`—write formatted output (integer only)

Synopsis

```
#include <stdio.h>
```

```
int iprintf(const char *format, ...);
```

Description

`iprintf` is a restricted version of `printf`: it has the same arguments and behavior, save that it cannot perform any floating-point formatting: the `f`, `g`, `G`, `e`, and `F` type specifiers are not recognized.

Returns

`iprintf` returns the number of bytes in the output string, save that the concluding `NULL` is not counted. `iprintf` returns when the end of the format string is encountered. If an error occurs, `iprintf` returns `EOF`.

Portability

`iprintf` is not required by ANSI C.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.25 mktemp, mkstemp—generate unused file name

Synopsis

```
#include <stdio.h>
char *mktemp(char *path);
int mkstemp(char *path);

char *_mktemp_r(void *reent, char *path);
int *_mkstemp_r(void *reent, char *path);
```

Description

`mktemp` and `mkstemp` attempt to generate a file name that is not yet in use for any existing file. `mkstemp` creates the file and opens it for reading and writing; `mktemp` simply generates the file name.

You supply a simple pattern for the generated file name, as the string at *path*. The pattern should be a valid filename (including path information if you wish) ending with some number of 'X' characters. The generated filename will match the leading part of the name you supply, with the trailing 'X' characters replaced by some combination of digits and letters.

The alternate functions `_mktemp_r` and `_mkstemp_r` are reentrant versions. The extra argument *reent* is a pointer to a reentrancy structure.

Returns

`mktemp` returns the pointer *path* to the modified string representing an unused filename, unless it could not generate one, or the pattern you provided is not suitable for a filename; in that case, it returns NULL.

`mkstemp` returns a file descriptor to the newly created file, unless it could not generate an unused filename, or the pattern you provided is not suitable for a filename; in that case, it returns -1.

Portability

ANSI C does not require either `mktemp` or `mkstemp`; the System V Interface Definition requires `mktemp` as of Issue 2.

Supporting OS subroutines required: `getpid`, `open`, `stat`.

3.26 perror—print an error message on standard error

Synopsis

```
#include <stdio.h>
void perror(char *prefix);

void _perror_r(void *reent, char *prefix);
```

Description

Use `perror` to print (on standard error) an error message corresponding to the current value of the global variable `errno`. Unless you use `NULL` as the value of the argument `prefix`, the error message will begin with the string at `prefix`, followed by a colon and a space (`:`). The remainder of the error message is one of the strings described for `strerror`.

The alternate function `_perror_r` is a reentrant version. The extra argument `reent` is a pointer to a reentrancy structure.

Returns

`perror` returns no result.

Portability

ANSI C requires `perror`, but the strings issued vary from one implementation to another. Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.27 `putc`—write a character (macro)

Synopsis

```
#include <stdio.h>
int putc(int ch, FILE *fp);
```

Description

`putc` is a macro, defined in `stdio.h`. `putc` writes the argument *ch* to the file or stream identified by *fp*, after converting it from an `int` to an **unsigned char**.

If the file was opened with append mode (or if the stream cannot support positioning), then the new character goes at the end of the file or stream. Otherwise, the new character is written at the current value of the position indicator, and the position indicator advances by one.

For a subroutine version of this macro, see `fputc`.

Returns

If successful, `putc` returns its argument *ch*. If an error intervenes, the result is EOF. You can use '`ferror(fp)`' to query for errors.

Portability

ANSI C requires `putc`; it suggests, but does not require, that `putc` be implemented as a macro. The standard explicitly permits macro implementations of `putc` to use the *fp* argument more than once; therefore, in a portable program, you should not use an expression with side effects as this argument.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.28 putchar—write a character (macro)

Synopsis

```
#include <stdio.h>
int putchar(int ch);

int _putchar_r(void *reent, int ch);
```

Description

`putchar` is a macro, defined in `stdio.h`. `putchar` writes its argument to the standard output stream, after converting it from an `int` to an `unsigned char`.

The alternate function `_putchar_r` is a reentrant version. The extra argument `reent` is a pointer to a reentrancy structure.

Returns

If successful, `putchar` returns its argument `ch`. If an error intervenes, the result is `EOF`. You can use `'ferror(stdin)'` to query for errors.

Portability

ANSI C requires `putchar`; it suggests, but does not require, that `putchar` be implemented as a macro.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.29 puts—write a character string

Synopsis

```
#include <stdio.h>
int puts(const char *s);

int _puts_r(void *reent, const char *s);
```

Description

`puts` writes the string at `s` (followed by a newline, instead of the trailing null) to the standard output stream.

The alternate function `_puts_r` is a reentrant version. The extra argument `reent` is a pointer to a reentrancy structure.

Returns

If successful, the result is a nonnegative integer; otherwise, the result is EOF.

Portability

ANSI C requires `puts`, but does not specify that the result on success must be 0; any non-negative value is permitted.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.30 putw—write a word (int)

Synopsis

```
#include <stdio.h>
int putw(int w, FILE *fp);
```

Description

`putw` is a function, defined in `stdio.h`. You can use `putw` to write a word to the file or stream identified by `fp`. As a side effect, `putw` advances the file's current position indicator. RETURNS Zero on success, EOF on failure.

Portability

`putw` is a remnant of K&R C, it is not part of any ISO C Standard. `fwrite` should be used instead. In fact, this implementation of `putw` is based upon `fwrite`.

Supporting OS subroutines required: `fwrite`.

3.31 remove—delete a file's name

Synopsis

```
#include <stdio.h>
int remove(char *filename);

int _remove_r(void *reent, char *filename);
```

Description

Use **remove** to dissolve the association between a particular filename (the string at *filename*) and the file it represents. After calling **remove** with a particular filename, you will no longer be able to open the file by that name.

In this implementation, you may use **remove** on an open file without error; existing file descriptors for the file will continue to access the file's data until the program using them closes the file.

The alternate function **_remove_r** is a reentrant version. The extra argument *reent* is a pointer to a reentrancy structure.

Returns

remove returns 0 if it succeeds, -1 if it fails.

Portability

ANSI C requires **remove**, but only specifies that the result on failure be nonzero. The behavior of **remove** when you call it on an open file may vary among implementations.

Supporting OS subroutine required: **unlink**.

3.32 rename—rename a file

Synopsis

```
#include <stdio.h>
int rename(const char *old, const char *new);

int _rename_r(void *reent,
              const char *old, const char *new);
```

Description

Use `rename` to establish a new name (the string at `new`) for a file now known by the string at `old`. After a successful `rename`, the file is no longer accessible by the string at `old`.

If `rename` fails, the file named `*old` is unaffected. The conditions for failure depend on the host operating system.

The alternate function `_rename_r` is a reentrant version. The extra argument `reent` is a pointer to a reentrancy structure.

Returns

The result is either 0 (when successful) or -1 (when the file could not be renamed).

Portability

ANSI C requires `rename`, but only specifies that the result on failure be nonzero. The effects of using the name of an existing file as `*new` may vary from one implementation to another.

Supporting OS subroutines required: `link`, `unlink`, or `rename`.

3.33 `rewind`—reinitialize a file or stream

Synopsis

```
#include <stdio.h>
void rewind(FILE *fp);
void _rewind_r(struct _reent *ptr, FILE *fp);
```

Description

`rewind` returns the file position indicator (if any) for the file or stream identified by *fp* to the beginning of the file. It also clears any error indicator and flushes any pending output.

Returns

`rewind` does not return a result.

Portability

ANSI C requires `rewind`.

No supporting OS subroutines are required.

3.34 `setbuf`—specify full buffering for a file or stream

Synopsis

```
#include <stdio.h>
void setbuf(FILE *fp, char *buf);
```

Description

`setbuf` specifies that output to the file or stream identified by *fp* should be fully buffered. All output for this file will go to a buffer (of size `BUFSIZ`, specified in ‘`stdio.h`’). Output will be passed on to the host system only when the buffer is full, or when an input operation intervenes.

You may, if you wish, supply your own buffer by passing a pointer to it as the argument *buf*. It must have size `BUFSIZ`. You can also use `NULL` as the value of *buf*, to signal that the `setbuf` function is to allocate the buffer.

Warnings

You may only use `setbuf` before performing any file operation other than opening the file. If you supply a non-null *buf*, you must ensure that the associated storage continues to be available until you close the stream identified by *fp*.

Returns

`setbuf` does not return a result.

Portability

Both ANSI C and the System V Interface Definition (Issue 2) require `setbuf`. However, they differ on the meaning of a `NULL` buffer pointer: the SVID issue 2 specification says that a `NULL` buffer pointer requests unbuffered output. For maximum portability, avoid `NULL` buffer pointers.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.35 setvbuf—specify file or stream buffering

Synopsis

```
#include <stdio.h>
int setvbuf(FILE *fp, char *buf,
            int mode, size_t size);
```

Description

Use `setvbuf` to specify what kind of buffering you want for the file or stream identified by `fp`, by using one of the following values (from `stdio.h`) as the `mode` argument:

- `_IONBF` Do not use a buffer: send output directly to the host system for the file or stream identified by `fp`.
- `_IOFBF` Use full output buffering: output will be passed on to the host system only when the buffer is full, or when an input operation intervenes.
- `_IOLBF` Use line buffering: pass on output to the host system at every newline, as well as when the buffer is full, or when an input operation intervenes.

Use the `size` argument to specify how large a buffer you wish. You can supply the buffer itself, if you wish, by passing a pointer to a suitable area of memory as `buf`. Otherwise, you may pass `NULL` as the `buf` argument, and `setvbuf` will allocate the buffer.

Warnings

You may only use `setvbuf` before performing any file operation other than opening the file. If you supply a non-null `buf`, you must ensure that the associated storage continues to be available until you close the stream identified by `fp`.

Returns

A 0 result indicates success, EOF failure (invalid `mode` or `size` can cause failure).

Portability

Both ANSI C and the System V Interface Definition (Issue 2) require `setvbuf`. However, they differ on the meaning of a `NULL` buffer pointer: the SVID issue 2 specification says that a `NULL` buffer pointer requests unbuffered output. For maximum portability, avoid `NULL` buffer pointers.

Both specifications describe the result on failure only as a nonzero value.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.36 `siprintf`—write formatted output (integer only)

Synopsis

```
#include <stdio.h>
```

```
int siprintf(char *str, const char *format [, arg, ...]);
```

Description

`siprintf` is a restricted version of `sprintf`: it has the same arguments and behavior, save that it cannot perform any floating-point formatting: the `f`, `g`, `G`, `e`, and `F` type specifiers are not recognized.

Returns

`siprintf` returns the number of bytes in the output string, save that the concluding `NULL` is not counted. `siprintf` returns when the end of the format string is encountered.

Portability

`siprintf` is not required by ANSI C.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.37 printf, fprintf, asprintf, sprintf, snprintf—format output

Synopsis

```
#include <stdio.h>

int printf(const char *format [, arg, ...]);
int fprintf(FILE *fd, const char *format [, arg, ...]);
int sprintf(char *str, const char *format [, arg, ...]);
int asprintf(char **strp, const char *format [, arg, ...]);
int snprintf(char *str, size_t size, const char *format [, arg, ...]);
```

Description

printf accepts a series of arguments, applies to each a format specifier from **format*, and writes the formatted data to **stdout**, terminated with a null character. The behavior of **printf** is undefined if there are not enough arguments for the format. **printf** returns when it reaches the end of the format string. If there are more arguments than the format requires, excess arguments are ignored.

fprintf, **asprintf**, **sprintf** and **snprintf** are identical to **printf**, other than the destination of the formatted output: **fprintf** sends the output to a specified file *fd*, while **asprintf** stores the output in a dynamically allocated buffer, while **sprintf** stores the output in the specified char array *str* and **snprintf** limits number of characters written to *str* to at most *size* (including terminating 0). For **sprintf** and **snprintf**, the behavior is undefined if the output **str* overlaps with one of the arguments. For **asprintf**, *strp* points to a pointer to char which is filled in with the dynamically allocated buffer. *format* is a pointer to a character string containing two types of objects: ordinary characters (other than %), which are copied unchanged to the output, and conversion specifications, each of which is introduced by %. (To include % in the output, use %% in the format string.) A conversion specification has the following form:

```
%[flags][width][.prec][size][type]
```

The fields of the conversion specification have the following meanings:

- *flags*
 - an optional sequence of characters which control output justification, numeric signs, decimal points, trailing zeroes, and octal and hex prefixes. The flag characters are minus (-), plus (+), space (), zero (0), and sharp (#). They can appear in any combination.
 - The result of the conversion is left justified, and the right is padded with blanks. If you do not use this flag, the result is right justified, and padded on the left.
 - + The result of a signed conversion (as determined by *type*) will always begin with a plus or minus sign. (If you do not use this flag, positive values do not begin with a plus sign.)
 - " " (space) If the first character of a signed conversion specification is not a sign, or if a signed conversion results in no characters, the result will begin with a space. If the space () flag and the plus (+) flag both appear, the space flag is ignored.

0	If the <i>type</i> character is d , i , o , u , x , X , e , E , f , g , or G : leading zeroes, are used to pad the field width (following any indication of sign or base); no spaces are used for padding. If the zero (0) and minus (-) flags both appear, the zero (0) flag will be ignored. For d , i , o , u , x , and X conversions, if a precision <i>prec</i> is specified, the zero (0) flag is ignored. Note that 0 is interpreted as a flag, not as the beginning of a field width.
#	The result is to be converted to an alternative form, according to the next character:
0	increases precision to force the first digit of the result to be a zero.
x	a non-zero result will have a 0x prefix.
X	a non-zero result will have a 0X prefix.
e, E or f	The result will always contain a decimal point even if no digits follow the point. (Normally, a decimal point appears only if a digit follows it.) Trailing zeroes are removed.
g or G	same as e or E, but trailing zeroes are not removed.
all others	undefined.

- *width*

width is an optional minimum field width. You can either specify it directly as a decimal integer, or indirectly by using instead an asterisk (*), in which case an `int` argument is used as the field width. Negative field widths are not supported; if you attempt to specify a negative field width, it is interpreted as a minus (-) flag followed by a positive field width.

- *prec*

an optional field; if present, it is introduced with '.' (a period). This field gives the maximum number of characters to print in a conversion; the minimum number of digits of an integer to print, for conversions with *type* **d**, **i**, **o**, **u**, **x**, and **X**; the maximum number of significant digits, for the **g** and **G** conversions; or the number of digits to print after the decimal point, for **e**, **E**, and **f** conversions. You can specify the precision either directly as a decimal integer or indirectly by using an asterisk (*), in which case an `int` argument is used as the precision. Supplying a negative precision is equivalent to omitting the precision. If only a period is specified the precision is zero. If a precision appears with any other conversion *type* than those listed here, the behavior is undefined.

- *size*

h, **l**, and **L** are optional size characters which override the default way that `printf` interprets the data type of the corresponding argument. **h** forces the following **d**, **i**, **o**, **u**, **x** or **X** conversion *type* to apply to a **short** or **unsigned short**. **h** also forces a following **n** *type* to apply to a pointer to a **short**. Similarly, an **l** forces the following **d**, **i**, **o**, **u**, **x** or **X** conversion *type* to apply to a **long** or **unsigned long**. **l** also forces a following **n** *type* to apply to a pointer to a **long**. **l** with **c**, **s** is equivalent to **C**, **S**

respectively. If an `h` or an `l` appears with another conversion specifier, the behavior is undefined. `L` forces a following `e`, `E`, `f`, `g` or `G` conversion *type* to apply to a long double argument. If `L` appears with any other conversion *type*, the behavior is undefined.

- *type*

type specifies what kind of conversion `printf` performs. Here is a table of these:

<code>%</code>	prints the percent character (<code>%</code>)
<code>c</code>	prints <i>arg</i> as single character
<code>C</code>	prints <code>wchar_t</code> <i>arg</i> as single multibyte character
<code>s</code>	prints characters until precision is reached or a null terminator is encountered; takes a string pointer
<code>S</code>	converts <code>wchar_t</code> characters to multibyte output characters until precision is reached or a null <code>wchar_t</code> terminator is encountered; takes a <code>wchar_t</code> pointer
<code>d</code>	prints a signed decimal integer; takes an <code>int</code> (same as <code>i</code>)
<code>i</code>	prints a signed decimal integer; takes an <code>int</code> (same as <code>d</code>)
<code>o</code>	prints a signed octal integer; takes an <code>int</code>
<code>u</code>	prints an unsigned decimal integer; takes an <code>int</code>
<code>x</code>	prints an unsigned hexadecimal integer (using <code>abcdef</code> as digits beyond 9); takes an <code>int</code>
<code>X</code>	prints an unsigned hexadecimal integer (using <code>ABCDEF</code> as digits beyond 9); takes an <code>int</code>
<code>f</code>	prints a signed value of the form <code>[-]9999.9999</code> ; takes a floating-point number
<code>e</code>	prints a signed value of the form <code>[-]9.9999e[+ -]999</code> ; takes a floating-point number
<code>E</code>	prints the same way as <code>e</code> , but using <code>E</code> to introduce the exponent; takes a floating-point number
<code>g</code>	prints a signed value in either <code>f</code> or <code>e</code> form, based on given value and precision—trailing zeros and the decimal point are printed only if necessary; takes a floating-point number
<code>G</code>	prints the same way as <code>g</code> , but using <code>E</code> for the exponent if an exponent is needed; takes a floating-point number
<code>n</code>	stores (in the same object) a count of the characters written; takes a pointer to <code>int</code>
<code>p</code>	prints a pointer in an implementation-defined format. This implementation treats the pointer as an <code>unsigned long</code> (same as <code>Lu</code>).

Returns

`sprintf` and `asprintf` return the number of bytes in the output string, save that the concluding NULL is not counted. `printf` and `fprintf` return the number of characters transmitted. If an error occurs, `printf` and `fprintf` return EOF and `asprintf` returns -1. No error returns occur for `sprintf`.

Portability

The ANSI C standard specifies that implementations must support at least formatted output of up to 509 characters.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.38 scanf, fscanf, sscanf—scan and format input

Synopsis

```
#include <stdio.h>

int scanf(const char *format [, arg, ...]);
int fscanf(FILE *fd, const char *format [, arg, ...]);
int sscanf(const char *str, const char *format
           [, arg, ...]);

int _scanf_r(struct _reent *ptr, const char *format [, arg, ...]);
int _fscanf_r(struct _reent *ptr, FILE *fd, const char *format [, arg, ...]);
int _sscanf_r(struct _reent *ptr, const char *str, const char *format
             [, arg, ...]);
```

Description

scanf scans a series of input fields from standard input, one character at a time. Each field is interpreted according to a format specifier passed to **scanf** in the format string at **format*. **scanf** stores the interpreted input from each field at the address passed to it as the corresponding argument following *format*. You must supply the same number of format specifiers and address arguments as there are input fields.

There must be sufficient address arguments for the given format specifiers; if not the results are unpredictable and likely disastrous. Excess address arguments are merely ignored.

scanf often produces unexpected results if the input diverges from an expected pattern. Since the combination of **gets** or **fgets** followed by **sscanf** is safe and easy, that is the preferred way to be certain that a program is synchronized with input at the end of a line.

fscanf and **sscanf** are identical to **scanf**, other than the source of input: **fscanf** reads from a file, and **sscanf** from a string.

The routines **_scanf_r**, **_fscanf_r**, and **_sscanf_r** are reentrant versions of **scanf**, **fscanf**, and **sscanf** that take an additional first argument pointing to a reentrancy structure.

The string at **format* is a character sequence composed of zero or more directives. Directives are composed of one or more whitespace characters, non-whitespace characters, and format specifications.

Whitespace characters are blank (), tab (\t), or newline (\n). When **scanf** encounters a whitespace character in the format string it will read (but not store) all consecutive whitespace characters up to the next non-whitespace character in the input.

Non-whitespace characters are all other ASCII characters except the percent sign (%). When **scanf** encounters a non-whitespace character in the format string it will read, but not store a matching non-whitespace character.

Format specifications tell **scanf** to read and convert characters from the input field into specific types of values, and store them in the locations specified by the address arguments.

Trailing whitespace is left unread unless explicitly matched in the format string.

The format specifiers must begin with a percent sign (%) and have the following form:

```
%[*][width][size]type
```

Each format specification begins with the percent character (%). The other fields are:

***** an optional marker; if present, it suppresses interpretation and assignment of this input field.

width an optional maximum field width: a decimal integer, which controls the maximum number of characters that will be read before converting the current input field. If the input field has fewer than *width* characters, `scanf` reads all the characters in the field, and then proceeds with the next field and its format specification.

If a whitespace or a non-convertable character occurs before *width* character are read, the characters up to that character are read, converted, and stored. Then `scanf` proceeds to the next format specification.

size `h`, `l`, and `L` are optional size characters which override the default way that `scanf` interprets the data type of the corresponding argument.

Modifier	Type(s)	
<code>hh</code>	<code>d, i, o, u, x, n</code>	convert input to char, store in char object
<code>h</code>	<code>d, i, o, u, x, n</code>	convert input to short, store in short object
<code>h</code>	<code>D, I, O, U, X</code> <code>e, f, c, s, p</code>	no effect
<code>l</code>	<code>d, i, o, u, x, n</code>	convert input to long, store in long object
<code>l</code>	<code>e, f, g</code>	convert input to double store in a double object
<code>l</code>	<code>D, I, O, U, X</code> <code>c, s, p</code>	no effect
<code>ll</code>	<code>d, i, o, u, x, n</code>	convert to long long, store in long long
<code>L</code>	<code>d, i, o, u, x, n</code>	convert to long long, store in long long
<code>L</code>	<code>e, f, g, E, G</code>	convert to long double, store in long double
<code>L</code>	all others	no effect

type

A character to specify what kind of conversion `scanf` performs. Here is a table of the conversion characters:

<code>%</code>	No conversion is done; the percent character (<code>%</code>) is stored.
<code>c</code>	Scans one character. Corresponding <i>arg</i> : (<code>char *arg</code>).
<code>s</code>	Reads a character string into the array supplied. Corresponding <i>arg</i> : (<code>char arg[]</code>).

[<i>pattern</i>]	Reads a non-empty character string into memory starting at <i>arg</i> . This area must be large enough to accept the sequence and a terminating null character which will be added automatically. (<i>pattern</i> is discussed in the paragraph following this table). Corresponding <i>arg</i> : (<code>char *arg</code>).
d	Reads a decimal integer into the corresponding <i>arg</i> : (<code>int *arg</code>).
D	Reads a decimal integer into the corresponding <i>arg</i> : (<code>long *arg</code>).
o	Reads an octal integer into the corresponding <i>arg</i> : (<code>int *arg</code>).
O	Reads an octal integer into the corresponding <i>arg</i> : (<code>long *arg</code>).
u	Reads an unsigned decimal integer into the corresponding <i>arg</i> : (<code>unsigned int *arg</code>).
U	Reads an unsigned decimal integer into the corresponding <i>arg</i> : (<code>unsigned long *arg</code>).
x,X	Read a hexadecimal integer into the corresponding <i>arg</i> : (<code>int *arg</code>).
e, f, g	Read a floating-point number into the corresponding <i>arg</i> : (<code>float *arg</code>).
E, F, G	Read a floating-point number into the corresponding <i>arg</i> : (<code>double *arg</code>).
i	Reads a decimal, octal or hexadecimal integer into the corresponding <i>arg</i> : (<code>int *arg</code>).
I	Reads a decimal, octal or hexadecimal integer into the corresponding <i>arg</i> : (<code>long *arg</code>).
n	Stores the number of characters read in the corresponding <i>arg</i> : (<code>int *arg</code>).
p	Stores a scanned pointer. ANSI C leaves the details to each implementation; this implementation treats <code>%p</code> exactly the same as <code>%U</code> . Corresponding <i>arg</i> : (<code>void **arg</code>).

A *pattern* of characters surrounded by square brackets can be used instead of the `s` type character. *pattern* is a set of characters which define a search set of possible characters making up the `scanf` input field. If the first character in the brackets is a caret (`^`), the search set is inverted to include all ASCII characters except those between the brackets. There is also a range facility which you can use as a shortcut. `%[0-9]` matches all decimal digits. The hyphen must not be the first or last character in the set. The character prior to the hyphen must be lexically less than the character after it.

Here are some *pattern* examples:

`%[abcd]` matches strings containing only a, b, c, and d.

`%[^abcd]` matches strings containing any characters except a, b, c, or d

`%[A-DW-Z]` matches strings containing A, B, C, D, W, X, Y, Z

`%[z-a]` matches the characters z, -, and a

Floating point numbers (for field types e, f, g, E, F, G) must correspond to the following general form:

`[+/-] dddd[.]ddd [E|e[+|-]ddd]`

where objects inclosed in square brackets are optional, and ddd represents decimal, octal, or hexadecimal digits.

Returns

`scanf` returns the number of input fields successfully scanned, converted and stored; the return value does not include scanned fields which were not stored.

If `scanf` attempts to read at end-of-file, the return value is EOF.

If no fields were stored, the return value is 0.

`scanf` might stop scanning a particular field before reaching the normal field end character, or may terminate entirely.

`scanf` stops scanning and storing the current field and moves to the next input field (if any) in any of the following situations:

- The assignment suppressing character (*) appears after the % in the format specification; the current input field is scanned but not stored.
- *width* characters have been read (*width* is a width specification, a positive decimal integer).
- The next character read cannot be converted under the the current format (for example, if a Z is read when the format is decimal).
- The next character in the input field does not appear in the search set (or does appear in the inverted search set).

When `scanf` stops scanning the current input field for one of these reasons, the next character is considered unread and used as the first character of the following input field, or the first character in a subsequent read operation on the input.

`scanf` will terminate under the following circumstances:

- The next character in the input field conflicts with a corresponding non-whitespace character in the format string.
- The next character in the input field is EOF.
- The format string has been exhausted.

When the format string contains a character sequence that is not part of a format specification, the same character sequence must appear in the input; `scanf` will scan but not store the matched characters. If a conflict occurs, the first conflicting character remains in the input as if it had never been read.

Portability

`scanf` is ANSI C.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

3.39 tmpfile—create a temporary file

Synopsis

```
#include <stdio.h>
FILE *tmpfile(void);

FILE *_tmpfile_r(void *reent);
```

Description

Create a temporary file (a file which will be deleted automatically), using a name generated by `tmpnam`. The temporary file is opened with the mode `"wb+"`, permitting you to read and write anywhere in it as a binary file (without any data transformations the host system may perform for text files).

The alternate function `_tmpfile_r` is a reentrant version. The argument *reent* is a pointer to a reentrancy structure.

Returns

`tmpfile` normally returns a pointer to the temporary file. If no temporary file could be created, the result is `NULL`, and `errno` records the reason for failure.

Portability

Both ANSI C and the System V Interface Definition (Issue 2) require `tmpfile`.

Supporting OS subroutines required: `close`, `fstat`, `getpid`, `isatty`, `lseek`, `open`, `read`, `sbrk`, `write`.

`tmpfile` also requires the global pointer `environ`.

3.40 tmpnam, tempnam—name for a temporary file

Synopsis

```
#include <stdio.h>
char *tmpnam(char *s);
char *tempnam(char *dir, char *pfx);
char *_tmpnam_r(void *reent, char *s);
char *_tempnam_r(void *reent, char *dir, char *pfx);
```

Description

Use either of these functions to generate a name for a temporary file. The generated name is guaranteed to avoid collision with other files (for up to TMP_MAX calls of either function). `tmpnam` generates file names with the value of `P_tmpdir` (defined in 'stdio.h') as the leading directory component of the path.

You can use the `tmpnam` argument `s` to specify a suitable area of memory for the generated filename; otherwise, you can call `tmpnam(NULL)` to use an internal static buffer.

`tempnam` allows you more control over the generated filename: you can use the argument `dir` to specify the path to a directory for temporary files, and you can use the argument `pfx` to specify a prefix for the base filename.

If `dir` is `NULL`, `tempnam` will attempt to use the value of environment variable `TMPDIR` instead; if there is no such value, `tempnam` uses the value of `P_tmpdir` (defined in 'stdio.h').

If you don't need any particular prefix to the basename of temporary files, you can pass `NULL` as the `pfx` argument to `tempnam`.

`_tmpnam_r` and `_tempnam_r` are reentrant versions of `tmpnam` and `tempnam` respectively. The extra argument `reent` is a pointer to a reentrancy structure.

Warnings

The generated filenames are suitable for temporary files, but do not in themselves make files temporary. Files with these names must still be explicitly removed when you no longer want them.

If you supply your own data area `s` for `tmpnam`, you must ensure that it has room for at least `L_tmpnam` elements of type `char`.

Returns

Both `tmpnam` and `tempnam` return a pointer to the newly generated filename.

Portability

ANSI C requires `tmpnam`, but does not specify the use of `P_tmpdir`. The System V Interface Definition (Issue 2) requires both `tmpnam` and `tempnam`.

Supporting OS subroutines required: `close`, `fstat`, `getpid`, `isatty`, `lseek`, `open`, `read`, `sbrk`, `write`.

The global pointer `environ` is also required.

3.41 `vprintf`, `vfprintf`, `vsprintf`—format argument list

Synopsis

```
#include <stdio.h>
#include <stdarg.h>
int vprintf(const char *fmt, va_list list);
int vfprintf(FILE *fp, const char *fmt, va_list list);
int vsprintf(char *str, const char *fmt, va_list list);
int vasprintf(char **strp, const char *fmt, va_list list);
int vsnprintf(char *str, size_t size, const char *fmt, va_list list);

int _vprintf_r(void *reent, const char *fmt,
               va_list list);
int _vfprintf_r(void *reent, FILE *fp, const char *fmt,
                va_list list);
int _vasprintf_r(void *reent, char **str, const char *fmt,
                 va_list list);
int _vsprintf_r(void *reent, char *str, const char *fmt,
                 va_list list);
int _vsnprintf_r(void *reent, char *str, size_t size, const char *fmt,
                  va_list list);
```

Description

`vprintf`, `vfprintf`, `vasprintf`, `vsprintf` and `vsnprintf` are (respectively) variants of `printf`, `fprintf`, `asprintf`, `sprintf`, and `snprintf`. They differ only in allowing their caller to pass the variable argument list as a `va_list` object (initialized by `va_start`) rather than directly accepting a variable number of arguments.

Returns

The return values are consistent with the corresponding functions: `vasprintf`/`vsprintf` returns the number of bytes in the output string, save that the concluding `NULL` is not counted. `vprintf` and `vfprintf` return the number of characters transmitted. If an error occurs, `vprintf` and `vfprintf` return `EOF` and `vasprintf` returns `-1`. No error returns occur for `vsprintf`.

Portability

ANSI C requires all three functions.

Supporting OS subroutines required: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`.

4 Strings and Memory (`'string.h'`)

This chapter describes string-handling functions and functions for managing areas of memory. The corresponding declarations are in `'string.h'`.

4.1 bcmp—compare two memory areas

Synopsis

```
#include <string.h>
int bcmp(const void *s1, const void *s2, size_t n);
```

Description

This function compares not more than *n* bytes of the object pointed to by *s1* with the object pointed to by *s2*.

This function is identical to `memcmp`.

Returns

The function returns an integer greater than, equal to or less than zero according to whether the object pointed to by *s1* is greater than, equal to or less than the object pointed to by *s2*.

Portability

`bcmp` requires no supporting OS subroutines.

4.2 bcopy—copy memory regions

Synopsis

```
#include <string.h>
void bcopy(const void *in, void *out, size_t n);
```

Description

This function copies *n* bytes from the memory region pointed to by *in* to the memory region pointed to by *out*.

This function is implemented in term of `memmove`.

Portability

`bcopy` requires no supporting OS subroutines.

4.3 bzero—initialize memory to zero

Synopsis

```
#include <string.h>
void bzero(void *b, size_t length);
```

Description

`bzero` initializes *length* bytes of memory, starting at address *b*, to zero.

Returns

`bzero` does not return a result.

Portability

`bzero` is in the Berkeley Software Distribution. Neither ANSI C nor the System V Interface Definition (Issue 2) require `bzero`.

`bzero` requires no supporting OS subroutines.

4.4 index—search for character in string

Synopsis

```
#include <string.h>
char * index(const char *string, int c);
```

Description

This function finds the first occurrence of *c* (converted to a char) in the string pointed to by *string* (including the terminating null character).

This function is identical to `strchr`.

Returns

Returns a pointer to the located character, or a null pointer if *c* does not occur in *string*.

Portability

`index` requires no supporting OS subroutines.

4.5 memccpy—copy memory regions with end-token check

Synopsis

```
#include <string.h>
void* memccpy(void *out, const void *in,
              int endchar, size_t n);
```

Description

This function copies up to *n* bytes from the memory region pointed to by *in* to the memory region pointed to by *out*. If a byte matching the *endchar* is encountered, the byte is copied and copying stops.

If the regions overlap, the behavior is undefined.

Returns

memccpy returns a pointer to the first byte following the *endchar* in the *out* region. If no byte matching *endchar* was copied, then NULL is returned.

Portability

memccpy is a GNU extension.

memccpy requires no supporting OS subroutines.

4.6 memchr—find character in memory

Synopsis

```
#include <string.h>
void *memchr(const void *src, int c, size_t length);
```

Description

This function searches memory starting at **src* for the character *c*. The search only ends with the first occurrence of *c*, or after *length* characters; in particular, NULL does not terminate the search.

Returns

If the character *c* is found within *length* characters of **src*, a pointer to the character is returned. If *c* is not found, then NULL is returned.

Portability

memchr is ANSI C.

memchr requires no supporting OS subroutines.

4.7 memcmp—compare two memory areas

Synopsis

```
#include <string.h>
int memcmp(const void *s1, const void *s2, size_t n);
```

Description

This function compares not more than *n* characters of the object pointed to by *s1* with the object pointed to by *s2*.

Returns

The function returns an integer greater than, equal to or less than zero according to whether the object pointed to by *s1* is greater than, equal to or less than the object pointed to by *s2*.

Portability

memcmp is ANSI C.

memcmp requires no supporting OS subroutines.

4.8 memcpy—copy memory regions

Synopsis

```
#include <string.h>
void* memcpy(void *out, const void *in, size_t n);
```

Description

This function copies *n* bytes from the memory region pointed to by *in* to the memory region pointed to by *out*.

If the regions overlap, the behavior is undefined.

Returns

`memcpy` returns a pointer to the first byte of the *out* region.

Portability

`memcpy` is ANSI C.

`memcpy` requires no supporting OS subroutines.

4.9 memmove—move possibly overlapping memory

Synopsis

```
#include <string.h>
void *memmove(void *dst, const void *src, size_t length);
```

Description

This function moves *length* characters from the block of memory starting at **src* to the memory starting at **dst*. *memmove* reproduces the characters correctly at **dst* even if the two areas overlap.

Returns

The function returns *dst* as passed.

Portability

memmove is ANSI C.

memmove requires no supporting OS subroutines.

4.10 mempcpy—copy memory regions and return end pointer

Synopsis

```
#include <string.h>
void* mempcpy(void *out, const void *in, size_t n);
```

Description

This function copies *n* bytes from the memory region pointed to by *in* to the memory region pointed to by *out*.

If the regions overlap, the behavior is undefined.

Returns

`mempcpy` returns a pointer to the byte following the last byte copied to the *out* region.

Portability

`mempcpy` is a GNU extension.

`mempcpy` requires no supporting OS subroutines.

4.11 `memset`—set an area of memory

Synopsis

```
#include <string.h>
void *memset(const void *dst, int c, size_t length);
```

Description

This function converts the argument *c* into an unsigned char and fills the first *length* characters of the array pointed to by *dst* to the value.

Returns

`memset` returns the value of *m*.

Portability

`memset` is ANSI C.

`memset` requires no supporting OS subroutines.

4.12 rindex—reverse search for character in string

Synopsis

```
#include <string.h>
char * rindex(const char *string, int c);
```

Description

This function finds the last occurrence of *c* (converted to a char) in the string pointed to by *string* (including the terminating null character).

This function is identical to `strrchr`.

Returns

Returns a pointer to the located character, or a null pointer if *c* does not occur in *string*.

Portability

`rindex` requires no supporting OS subroutines.

4.13 `strcasemp`—case insensitive character string compare

Synopsis

```
#include <string.h>
int strcasemp(const char *a, const char *b);
```

Description

`strcasemp` compares the string at *a* to the string at *b* in a case-insensitive manner.

Returns

If **a* sorts lexicographically after **b* (after both are converted to upper case), `strcasemp` returns a number greater than zero. If the two strings match, `strcasemp` returns zero. If **a* sorts lexicographically before **b*, `strcasemp` returns a number less than zero.

Portability

`strcasemp` is in the Berkeley Software Distribution.

`strcasemp` requires no supporting OS subroutines. It uses `tolower()` from elsewhere in this library.

4.14 `strcat`—concatenate strings

Synopsis

```
#include <string.h>
char *strcat(char *dst, const char *src);
```

Description

`strcat` appends a copy of the string pointed to by *src* (including the terminating null character) to the end of the string pointed to by *dst*. The initial character of *src* overwrites the null character at the end of *dst*.

Returns

This function returns the initial value of *dst*.

Portability

`strcat` is ANSI C.

`strcat` requires no supporting OS subroutines.

4.15 strchr—search for character in string

Synopsis

```
#include <string.h>
char * strchr(const char *string, int c);
```

Description

This function finds the first occurrence of *c* (converted to a char) in the string pointed to by *string* (including the terminating null character).

Returns

Returns a pointer to the located character, or a null pointer if *c* does not occur in *string*.

Portability

`strchr` is ANSI C.

`strchr` requires no supporting OS subroutines.

4.16 strcmp—character string compare

Synopsis

```
#include <string.h>
int strcmp(const char *a, const char *b);
```

Description

`strcmp` compares the string at *a* to the string at *b*.

Returns

If **a* sorts lexicographically after **b*, `strcmp` returns a number greater than zero. If the two strings match, `strcmp` returns zero. If **a* sorts lexicographically before **b*, `strcmp` returns a number less than zero.

Portability

`strcmp` is ANSI C.

`strcmp` requires no supporting OS subroutines.

4.17 strcoll—locale specific character string compare

Synopsis

```
#include <string.h>
int strcoll(const char *stra, const char * strb);
```

Description

`strcoll` compares the string pointed to by *stra* to the string pointed to by *strb*, using an interpretation appropriate to the current `LC_COLLATE` state.

Returns

If the first string is greater than the second string, `strcoll` returns a number greater than zero. If the two strings are equivalent, `strcoll` returns zero. If the first string is less than the second string, `strcoll` returns a number less than zero.

Portability

`strcoll` is ANSI C.

`strcoll` requires no supporting OS subroutines.

4.18 `strcpy`—copy string

Synopsis

```
#include <string.h>
char *strcpy(char *dst, const char *src);
```

Description

`strcpy` copies the string pointed to by *src* (including the terminating null character) to the array pointed to by *dst*.

Returns

This function returns the initial value of *dst*.

Portability

`strcpy` is ANSI C.

`strcpy` requires no supporting OS subroutines.

4.19 `strcspn`—count chars not in string

Synopsis

```
size_t strcspn(const char *s1, const char *s2);
```

Description

This function computes the length of the initial part of the string pointed to by *s1* which consists entirely of characters *NOT* from the string pointed to by *s2* (excluding the terminating null character).

Returns

`strcspn` returns the length of the substring found.

Portability

`strcspn` is ANSI C.

`strcspn` requires no supporting OS subroutines.

4.20 strerror—convert error number to string

Synopsis

```
#include <string.h>
char *strerror(int errnum);
```

Description

`strerror` converts the error number *errnum* into a string. The value of *errnum* is usually a copy of `errno`. If *errnum* is not a known error number, the result points to an empty string. This implementation of `strerror` prints out the following strings for each of the values defined in 'errno.h':

E2BIG	Arg list too long
EACCES	Permission denied
EADDRINUSE	Address already in use
EADV	Advertise error
EAFNOSUPPORT	Address family not supported by protocol family
EAGAIN	No more processes
EALREADY	Socket already connected
EBADF	Bad file number
EBADMSG	Bad message
EBUSY	Device or resource busy
ECHILD	No children
ECOMM	Communication error
ECONNABORTED	Software caused connection abort
ECONNREFUSED	Connection refused
EDEADLK	Deadlock
EDESTADDRREQ	Destination address required
EEXIST	File exists
EDOM	Math argument
EFAULT	Bad address
EFBIG	File too large
EHOSTDOWN	Host is down

EHOSTUNREACH	Host is unreachable
EIDRM	Identifier removed
EINPROGRESS	Connection already in progress
EINTR	Interrupted system call
EINVAL	Invalid argument
EIO	I/O error
EISCONN	Socket is already connected
EISDIR	Is a directory
ELIBACC	Cannot access a needed shared library
ELIBBAD	Accessing a corrupted shared library
ELIBEXEC	Cannot exec a shared library directly
ELIBMAX	Attempting to link in more shared libraries than system limit
ELIBSCN	.lib section in a.out corrupted
EMFILE	Too many open files
EMLINK	Too many links
EMSGSIZE	Message too long
EMULTIHOP	Multihop attempted
ENAMETOOLONG	File or path name too long
ENETDOWN	Network interface not configured
ENETUNREACH	Network is unreachable
ENFILE	Too many open files in system
ENODEV	No such device
ENOENT	No such file or directory
ENOEXEC	Exec format error
ENOLCK	No lock
ENOLINK	Virtual circuit is gone
ENOMEM	Not enough space
ENOMSG	No message of desired type
ENONET	Machine is not on the network

ENOPKG	No package
ENOPROTOPT	Protocol not available
ENOSPC	No space left on device
ENOSR	No stream resources
ENOSTR	Not a stream
ENOSYS	Function not implemented
ENOTBLK	Block device required
ENOTCONN	Socket is not connected
ENOTDIR	Not a directory
ENOTEMPTY	Directory not empty
ENOTSOCK	Socket operation on non-socket
ENOTSUP	Not supported
ENOTTY	Not a character device
ENXIO	No such device or address
EPERM	Not owner
EPIPE	Broken pipe
EPROTO	Protocol error
EPROTOTYPE	Protocol wrong type for socket
EPRONOSUPPORT	Unknown protocol
ERANGE	Result too large
EREMOTE	Resource is remote
EROFS	Read-only file system
ESHUTDOWN	Can't send after socket shutdown
ESOCKTNOSUPPORT	Socket type not supported
ESPIPE	Illegal seek
ESRCH	No such process
ESRMNT	Srmount error
ETIME	Stream ioctl timeout

ETIMEDOUT	Connection timed out
ETXTBSY	Text file busy
EXDEV	Cross-device link

Returns

This function returns a pointer to a string. Your application must not modify that string.

Portability

ANSI C requires `strerror`, but does not specify the strings used for each error number.

Although this implementation of `strerror` is reentrant, ANSI C declares that subsequent calls to `strerror` may overwrite the result string; therefore portable code cannot depend on the reentrancy of this subroutine.

This implementation of `strerror` provides for user-defined extensibility. `errno.h` defines `__ELASTERERROR`, which can be used as a base for user-defined error values. If the user supplies a routine named `_user_strerror`, and `errnum` passed to `strerror` does not match any of the supported values, `_user_strerror` is called with `errnum` as its argument.

`_user_strerror` takes one argument of type `int`, and returns a character pointer. If `errnum` is unknown to `_user_strerror`, `_user_strerror` returns `NULL`. The default `_user_strerror` returns `NULL` for all input values.

`strerror` requires no supporting OS subroutines.

4.21 strlen—character string length

Synopsis

```
#include <string.h>
size_t strlen(const char *str);
```

Description

The `strlen` function works out the length of the string starting at `*str` by counting characters until it reaches a `NULL` character.

Returns

`strlen` returns the character count.

Portability

`strlen` is ANSI C.

`strlen` requires no supporting OS subroutines.

4.22 `strlwr`—force string to lower case

Synopsis

```
#include <string.h>
char *strlwr(char *a);
```

Description

`strlwr` converts each characters in the string at *a* to lower case.

Returns

`strlwr` returns its argument, *a*.

Portability

`strlwr` is not widely portable.

`strlwr` requires no supporting OS subroutines.

4.23 strncasecmp—case insensitive character string compare

Synopsis

```
#include <string.h>
int strncasecmp(const char *a, const char * b, size_t length);
```

Description

`strncasecmp` compares up to *length* characters from the string at *a* to the string at *b* in a case-insensitive manner.

Returns

If **a* sorts lexicographically after **b* (after both are converted to upper case), `strncasecmp` returns a number greater than zero. If the two strings are equivalent, `strncasecmp` returns zero. If **a* sorts lexicographically before **b*, `strncasecmp` returns a number less than zero.

Portability

`strncasecmp` is in the Berkeley Software Distribution.

`strncasecmp` requires no supporting OS subroutines. It uses `tolower()` from elsewhere in this library.

4.24 `strncat`—concatenate strings

Synopsis

```
#include <string.h>
char *strncat(char *dst, const char *src, size_t length);
```

Description

`strncat` appends not more than *length* characters from the string pointed to by *src* (including the terminating null character) to the end of the string pointed to by *dst*. The initial character of *src* overwrites the null character at the end of *dst*. A terminating null character is always appended to the result

Warnings

Note that a null is always appended, so that if the copy is limited by the *length* argument, the number of characters appended to *dst* is $n + 1$.

Returns

This function returns the initial value of *dst*

Portability

`strncat` is ANSI C.

`strncat` requires no supporting OS subroutines.

4.25 strncmp—character string compare

Synopsis

```
#include <string.h>
int strncmp(const char *a, const char * b, size_t length);
```

Description

strncmp compares up to *length* characters from the string at *a* to the string at *b*.

Returns

If **a* sorts lexicographically after **b*, strncmp returns a number greater than zero. If the two strings are equivalent, strncmp returns zero. If **a* sorts lexicographically before **b*, strncmp returns a number less than zero.

Portability

strncmp is ANSI C.

strncmp requires no supporting OS subroutines.

4.26 strncpy—counted copy string

Synopsis

```
#include <string.h>
char *strncpy(char *dst, const char *src, size_t length);
```

Description

`strncpy` copies not more than *length* characters from the the string pointed to by *src* (including the terminating null character) to the array pointed to by *dst*. If the string pointed to by *src* is shorter than *length* characters, null characters are appended to the destination array until a total of *length* characters have been written.

Returns

This function returns the initial value of *dst*.

Portability

`strncpy` is ANSI C.

`strncpy` requires no supporting OS subroutines.

4.27 strpbrk—find chars in string

Synopsis

```
#include <string.h>
char *strpbrk(const char *s1, const char *s2);
```

Description

This function locates the first occurrence in the string pointed to by *s1* of any character in string pointed to by *s2* (excluding the terminating null character).

Returns

`strpbrk` returns a pointer to the character found in *s1*, or a null pointer if no character from *s2* occurs in *s1*.

Portability

`strpbrk` requires no supporting OS subroutines.

4.28 strrchr—reverse search for character in string

Synopsis

```
#include <string.h>
char * strrchr(const char *string, int c);
```

Description

This function finds the last occurrence of *c* (converted to a char) in the string pointed to by *string* (including the terminating null character).

Returns

Returns a pointer to the located character, or a null pointer if *c* does not occur in *string*.

Portability

`strrchr` is ANSI C.

`strrchr` requires no supporting OS subroutines.

4.29 `strspn`—find initial match

Synopsis

```
#include <string.h>
size_t strspn(const char *s1, const char *s2);
```

Description

This function computes the length of the initial segment of the string pointed to by *s1* which consists entirely of characters from the string pointed to by *s2* (excluding the terminating null character).

Returns

`strspn` returns the length of the segment found.

Portability

`strspn` is ANSI C.

`strspn` requires no supporting OS subroutines.

4.30 strstr—find string segment

Synopsis

```
#include <string.h>
char *strstr(const char *s1, const char *s2);
```

Description

Locates the first occurrence in the string pointed to by *s1* of the sequence of characters in the string pointed to by *s2* (excluding the terminating null character).

Returns

Returns a pointer to the located string segment, or a null pointer if the string *s2* is not found. If *s2* points to a string with zero length, the *s1* is returned.

Portability

`strstr` is ANSI C.

`strstr` requires no supporting OS subroutines.

4.31 strtok, strtok_r, strsep—get next token from a string

Synopsis

```
#include <string.h>
char *strtok(char *source, const char *delimiters)
char *strtok_r(char *source, const char *delimiters,
               char **lasts)
char *strsep(char **source_ptr, const char *delimiters)
```

Description

The `strtok` function is used to isolate sequential tokens in a null-terminated string, `*source`. These tokens are delimited in the string by at least one of the characters in `*delimiters`. The first time that `strtok` is called, `*source` should be specified; subsequent calls, wishing to obtain further tokens from the same string, should pass a null pointer instead. The separator string, `*delimiters`, must be supplied each time, and may change between calls.

The `strtok` function returns a pointer to the beginning of each subsequent token in the string, after replacing the separator character itself with a NUL character. When no more tokens remain, a null pointer is returned.

The `strtok_r` function has the same behavior as `strtok`, except a pointer to placeholder `*[lasts>` must be supplied by the caller.

The `strsep` function is similar in behavior to `strtok`, except a pointer to the string pointer must be supplied [`source_ptr>` and the function does not skip leading delimiters. When the string starts with a delimiter, the delimiter is changed to the NUL character and the empty string is returned. Like `strtok_r` and `strtok`, the `*[source_ptr>` is updated to the next character following the last delimiter found or NULL if the end of string is reached with no more delimiters.

Returns

`strtok`, `strtok_r`, and `strsep` all return a pointer to the next token, or NULL if no more tokens can be found. For `strsep`, a token may be the empty string.

Portability

`strtok` is ANSI C. `strtok_r` is POSIX. `strsep` is a BSD-extension.

`strtok`, `strtok_r`, and `strsep` require no supporting OS subroutines.

4.32 `strupr`—force string to uppercase

Synopsis

```
#include <string.h>
char *strupr(char *a);
```

Description

`strupr` converts each characters in the string at *a* to upper case.

Returns

`strupr` returns its argument, *a*.

Portability

`strupr` is not widely portable.

`strupr` requires no supporting OS subroutines.

4.33 `strxfrm`—transform string

Synopsis

```
#include <string.h>
size_t strxfrm(char *s1, const char *s2, size_t n);
```

Description

This function transforms the string pointed to by *s2* and places the resulting string into the array pointed to by *s1*. The transformation is such that if the `strcmp` function is applied to the two transformed strings, it returns a value greater than, equal to, or less than zero, corresponding to the result of a `strcoll` function applied to the same two original strings. No more than *n* characters are placed into the resulting array pointed to by *s1*, including the terminating null character. If *n* is zero, *s1* may be a null pointer. If copying takes place between objects that overlap, the behavior is undefined.

With a C locale, this function just copies.

Returns

The `strxfrm` function returns the length of the transformed string (not including the terminating null character). If the value returned is *n* or more, the contents of the array pointed to by *s1* are indeterminate.

Portability

`strxfrm` is ANSI C.

`strxfrm` requires no supporting OS subroutines.

4.34 `swab`—swap adjacent bytes

Synopsis

```
#include <unistd.h>
void swab(const void *in, void *out, ssize_t n);
```

Description

This function copies *n* bytes from the memory region pointed to by *in* to the memory region pointed to by *out*, exchanging adjacent even and odd bytes.

Portability

`swab` requires no supporting OS subroutines.

5 Wide Character Strings (`wchar.h`)

This chapter describes wide-character string-handling functions and managing areas of memory containing wide-characters. The corresponding declarations are in `wchar.h`.

5.1 wmemchr—find a wide-character in memory

Synopsis

```
#include <wchar.h>
wchar_t *wmemchr(const wchar_t *s, wchar_t c, size_t n);
```

Description

The `wmemchr` function locates the first occurrence of `c` in the initial `n` wide-characters of the object pointed to be `s`. This function is not affected by locale and all `wchar_t` values are treated identically. The null wide-character and `wchar_t` values not corresponding to valid characters are not treated specially.

If `n` is zero, `s` must be a valid pointer and the function behaves as if no valid occurrence of `c` is found.

Returns

The `wmemchr` function returns a pointer to the located wide-character, or a null pointer if the wide-character does not occur in the object.

Portability

`wmemchr` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.2 wmemcmp—compare wide-characters in memory

Synopsis

```
#include <wchar.h>
int wmemcmp(const wchar_t *s1, const wchar_t *s2, size_t n);
```

Description

The `wmemcmp` function compares the first n wide-characters of the object pointed to by $s1$ to the first n wide-characters of the object pointed to by $s2$. This function is not affected by locale and all `wchar_t` values are treated identically. The null wide-character and `wchar_t` values not corresponding to valid characters are not treated specially.

If n is zero, $s1$ and $s2$ must be a valid pointers and the function behaves as if the two objects compare equal.

Returns

The `wmemcmp` function returns an integer greater than, equal to, or less than zero, accordingly as the object pointed to by $s1$ is greater than, equal to, or less than the object pointed to by $s2$.

Portability

`wmemcmp` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.3 wmemcpy—copy wide-characters in memory

Synopsis

```
#include <wchar.h>
wchar_t *wmemcpy(wchar_t *d, const wchar_t *s, size_t n);
```

Description

The `wmemcpy` function copies n wide-characters from the object pointed to by s to the object pointed to be d . This function is not affected by locale and all `wchar_t` values are treated identically. The null wide-character and `wchar_t` values not corresponding to valid characters are not treated specially.

If n is zero, d and s must be a valid pointers, and the function copies zero wide-characters.

Returns

The `wmemcpy` function returns the value of d .

Portability

`wmemcpy` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.4 wmemmove—wmemmove - copy wide-characters in memory with overlapping areas

Synopsis

```
#include <wchar.h>
wchar_t *wmemmove(wchar_t *d, const wchar_t *s, size_t n);
```

Description

The `wmemmove` function copies n wide-characters from the object pointed to by s to the object pointed to by d . Copying takes place as if the n wide-characters from the object pointed to by s are first copied into a temporary array of n wide-characters that does not overlap the objects pointed to by d or s , and then the n wide-characters from the temporary array are copied into the object pointed to by d .

This function is not affected by locale and all `wchar_t` values are treated identically. The null wide-character and `wchar_t` values not corresponding to valid characters are not treated specially.

If n is zero, d and s must be a valid pointers, and the function copies zero wide-characters.

Returns

The `wmemmove` function returns the value of d .

Portability

`wmemmove` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.5 wmemset—set wide-characters in memory

Synopsis

```
#include <wchar.h>
wchar_t *wmemset(wchar_t *s, wchar_t c, size_t n);
```

Description

The `wmemset` function copies the value of `c` into each of the first `n` wide-characters of the object pointed to by `s`. This function is not affected by locale and all `wchar_t` values are treated identically. The null wide-character and `wchar_t` values not corresponding to valid characters are not treated specially.

If `n` is zero, `s` must be a valid pointer and the function copies zero wide-characters.

Returns

The `wmemset` functions returns the value of `s`.

Portability

`wmemset` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.6 wcscat—concatenate two wide-character strings

Synopsis

```
#include <wchar.h>
wchar_t *wcscat(wchar_t *s1, const wchar_t *s2);
```

Description

The `wcscat` function appends a copy of the wide-character string pointed to by `s2` (including the terminating null wide-character code) to the end of the wide-character string pointed to by `s1`. The initial wide-character code of `s2` overwrites the null wide-character code at the end of `s1`. If copying takes place between objects that overlap, the behaviour is undefined.

Returns

The `wcscat` function returns `s1`; no return value is reserved to indicate an error.

Portability

`wcscat` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.7 wcschr—wide-character string scanning operation

Synopsis

```
#include <wchar.h>
wchar_t *wcschr(const wchar_t *s, wchar_t c);
```

Description

The `wcschr` function locates the first occurrence of `c` in the wide-character string pointed to by `s`. The value of `c` must be a character representable as a type `wchar_t` and must be a wide-character code corresponding to a valid character in the current locale. The terminating null wide-character string.

Returns

Upon completion, `wcschr` returns a pointer to the wide-character code, or a null pointer if the wide-character code is not found.

Portability

`wcschr` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.8 wcsncmp—compare two wide-character strings

Synopsis

```
#include <wchar.h>
int wcsncmp(const wchar_t *s1, *s2);
```

Description

The `wcsncmp` function compares the wide-character string pointed to by `s1` to the wide-character string pointed to by `s2`.

The sign of a non-zero return value is determined by the sign of the difference between the values of the first pair of wide-character codes that differ in the objects being compared.

Returns

Upon completion, `wcsncmp` returns an integer greater than, equal to or less than 0, if the wide-character string pointed to by `s1` is greater than, equal to or less than the wide-character string pointed to by `s2` respectively.

Portability

`wcsncmp` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.9 wcs coll—locale specific wide-character string compare

Synopsis

```
#include <wchar.h>
int wcs coll(const wchar_t *stra, const wchar_t * strb);
```

Description

`wcs coll` compares the wide-character string pointed to by *stra* to the wide-character string pointed to by *strb*, using an interpretation appropriate to the current `LC_COLLATE` state.

The current implementation of `wcs coll` simply uses `wscmp` and does not support any language-specific sorting.

Returns

If the first string is greater than the second string, `wcs coll` returns a number greater than zero. If the two strings are equivalent, `wcs coll` returns zero. If the first string is less than the second string, `wcs coll` returns a number less than zero.

Portability

`wcs coll` is ISO/IEC 9899/AMD1:1995 (ISO C).

5.10 wcsncpy—copy a wide-character string

Synopsis

```
#include <wchar.h>
wchar_t *wcsncpy(wchar_t *s1, const wchar_t *,s2);
```

Description

The `wcsncpy` function copies the wide-character string pointed to by `s2` (including the terminating null wide-character code) into the array pointed to by `s1`. If copying takes place between objects that overlap, the behaviour is undefined.

Returns

The `wcsncpy` function returns `s1`; no return value is reserved to indicate an error.

Portability

`wcsncpy` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.11 `wcscspn`—get length of a complementary wide substring

Synopsis

```
#include <wchar.h>
size_t wcscspn(const wchar_t *s, wchar_t *set);
```

Description

The `wcscspn` function computes the length of the maximum initial segment of the wide-character string pointed to by `s` which consists entirely of wide-character codes not from the wide-character string pointed to by `set`.

Returns

The `wcscspn` function returns the length of the initial substring of `s`; no return value is reserved to indicate an error.

Portability

`wcscspn` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.12 wcs1cat—concatenate wide-character strings to specified length

Synopsis

```
#include <wchar.h>
size_t wcs1cat(wchar_t *dst, const wchar_t *src, size_t siz);
```

Description

The `wcs1cat` function appends wide-characters from `src` to end of the `dst` wide-character string so that the resultant wide-character string is not more than `siz` wide-characters including terminating null wide-character code. A terminating null wide-character is always added unless `siz` is 0. Thus, the maximum number of wide-characters that can be appended from `src` is `siz - 1`. If copying takes place between objects that overlap, the behaviour is undefined.

Returns

Wide-character string length of initial `dst` plus the wide-character string length of `src` (does not include terminating null wide-characters). If the return value is greater than or equal to `siz`, then truncation occurred and not all wide-characters from `src` were appended.

Portability

No supporting OS subroutines are required.

5.13 wcsncpy—copy a wide-character string to specified length

Synopsis

```
#include <wchar.h>
size_t wcsncpy(wchar_t *dst, const wchar_t *src, size_t siz);
```

Description

`wcsncpy` copies wide-characters from *src* to *dst* such that up to *siz* - 1 characters are copied. A terminating null is appended to the result, unless *siz* is zero.

Returns

`wcsncpy` returns the number of wide-characters in *src*, not including the terminating null wide-character. If the return value is greater than or equal to *siz*, then not all wide-characters were copied from *src* and truncation occurred.

Portability

No supporting OS subroutines are required.

5.14 wcslen—get wide-character string length

Synopsis

```
#include <wchar.h>
size_t wcslen(const wchar_t *s);
```

Description

The `wcslen` function computes the number of wide-character codes in the wide-character string to which `s` points, not including the terminating null wide-character code.

Returns

The `wcslen` function returns the length of `s`; no return value is reserved to indicate an error.

Portability

`wcslen` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.15 wcsncat—concatenate part of two wide-character strings

Synopsis

```
#include <wchar.h>
wchar_t *wcsncat(wchar_t *s1, const wchar_t *s2, size_t n);
```

Description

The `wcsncat` function appends not more than n wide-character codes (a null wide-character code and wide-character codes that follow it are not appended) from the array pointed to by $s2$ to the end of the wide-character string pointed to by $s1$. The initial wide-character code of $s2$ overwrites the null wide-character code at the end of $s1$. A terminating null wide-character code is always appended to the result. If copying takes place between objects that overlap, the behaviour is undefined.

Returns

The `wcsncat` function returns $s1$; no return value is reserved to indicate an error.

Portability

`wcsncat` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.16 wcsncmp—compare part of two wide-character strings

Synopsis

```
#include <wchar.h>
int wcsncmp(const wchar_t *s1, const wchar_t *s2, size_t n);
```

Description

The `wcsncmp` function compares not more than *n* wide-character codes (wide-character codes that follow a null wide-character code are not compared) from the array pointed to by *s1* to the array pointed to by *s2*.

The sign of a non-zero return value is determined by the sign of the difference between the values of the first pair of wide-character codes that differ in the objects being compared.

Returns

Upon successful completion, `wcsncmp` returns an integer greater than, equal to or less than 0, if the possibly null-terminated array pointed to by *s1* is greater than, equal to or less than the possibly null-terminated array pointed to by *s2* respectively.

Portability

`wcsncmp` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.17 wcsncpy—copy part of a wide-character string

Synopsis

```
#include <wchar.h>
wchar_t *wcsncpy(wchar_t *s1, const wchar_t *s2, size_t n);
```

Description

The `wcsncpy` function copies not more than `n` wide-character codes (wide-character codes that follow a null wide-character code are not copied) from the array pointed to by `s2` to the array pointed to by `s1`. If copying takes place between objects that overlap, the behaviour is undefined.

If the array pointed to by `s2` is a wide-character string that is shorter than `n` wide-character codes, null wide-character codes are appended to the copy in the array pointed to by `s1`, until `n` wide-character codes in all are written.

Returns

The `wcsncpy` function returns `s1`; no return value is reserved to indicate an error.

Portability

`wcsncpy` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.18 wcsnlen—get fixed-size wide character string length

Synopsis

```
#include <wchar.h>
size_t wcsnlen(const wchar_t *s, size_t maxlen);
```

Description

The `wcsnlen` function computes the number of wide character codes in the wide character string pointed to by `s` not including the terminating `L'\0'` wide character but at most `maxlen` wide characters.

Returns

`wcsnlen` returns the length of `s` if it is less than `maxlen`, or `maxlen` if there is no `L'\0'` wide character in first `maxlen` characters.

Portability

`wcsnlen` is GNU extension.. `wcsnlen` requires no supporting OS subroutines.

5.19 `wcspbrk`—scan wide-character string for a wide-character code

Synopsis

```
#include <wchar.h>
wchar_t *wcspbrk(const wchar_t *s, const wchar_t *set);
```

Description

The `wcspbrk` function locates the first occurrence in the wide-character string pointed to by *s* of any wide-character code from the wide-character string pointed to by *set*.

Returns

Upon successful completion, `wcspbrk` returns a pointer to the wide-character code or a null pointer if no wide-character code from *set* occurs in *s*.

Portability

`wcspbrk` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.20 wcsrchr—wide-character string scanning operation

Synopsis

```
#include <wchar.h>
wchar_t *wcsrchr(const wchar_t *s, wchar_t c);
```

Description

The `wcsrchr` function locates the last occurrence of `c` in the wide-character string pointed to by `s`. The value of `c` must be a character representable as a type `wchar_t` and must be a wide-character code corresponding to a valid character in the current locale. The terminating null wide-character code is considered to be part of the wide-character string.

Returns

Upon successful completion, `wcsrchr` returns a pointer to the wide-character code or a null pointer if `c` does not occur in the wide-character string.

Portability

`wcsrchr` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.21 wcssp—get length of a wide substring

Synopsis

```
#include <wchar.h>
size_t wcssp(const wchar_t *s, const wchar_t *set);
```

Description

The `wcssp` function computes the length of the maximum initial segment of the wide-character string pointed to by `s` which consists entirely of wide-character codes from the wide-character string pointed to by `set`.

Returns

The `wcssp()` function returns the length `s1`; no return value is reserved to indicate an error.

Portability

`wcssp` is ISO/IEC 9899/AMD1:1995 (ISO C). No supporting OS subroutines are required.

5.22 wcsstr—find a wide-character substring

Synopsis

```
#include <wchar.h>
wchar_t *wcsstr(const wchar_t *big, const wchar_t *little);
```

Description

The `wcsstr` function locates the first occurrence in the wide-character string pointed to by *big* of the sequence of wide-characters (excluding the terminating null wide-character) in the wide-character string pointed to by *little*.

Returns

On successful completion, `wcsstr` returns a pointer to the located wide-character string, or a null pointer if the wide-character string is not found.

If *little* points to a wide-character string with zero length, the function returns *big*.

Portability

`wcsstr` is ISO/IEC 9899/AMD1:1995 (ISO C).

5.23 `wcswidth`—number of column positions of a wide-character string

Synopsis

```
#include <wchar.h>
int wcswidth(const wchar_t *pwcs, size_t n);
```

Description

The `wcswidth` function shall determine the number of column positions required for `n` wide-character codes (or fewer than `n` wide-character codes if a null wide-character code is encountered before `n` wide-character codes are exhausted) in the string pointed to by `pwcs`.

Returns

The `wcswidth` function either shall return 0 (if `pwcs` points to a null wide-character code), or return the number of column positions to be occupied by the wide-character string pointed to by `pwcs`, or return -1 (if any of the first `n` wide-character codes in the wide-character string pointed to by `pwcs` is not a printable wide-character code).

Portability

`wcswidth` has been introduced in the Single UNIX Specification Volume 2 `wcswidth` has been marked as extension in Single UNIX Specification Volume 3

5.24 `wcwidth`—number of column positions of a wide-character code

Synopsis

```
#include <wchar.h>
int wcwidth(const wchar_t wc);
```

Description

The `wcwidth` function shall determine the number of column positions required for the wide character `wc`. The application shall ensure that the value of `wc` is a character representable as a `wchar_t`, and is a wide-character code corresponding to a valid character in the current locale.

Returns

The `wcwidth` function shall either return 0 (if `wc` is a null wide-character code), or return the number of column positions to be occupied by the wide-character code `wc`, or return -1 (if `wc` does not correspond to a printable wide-character code).

The current implementation of `wcwidth` simply sets the width of all printable characters to 1 since newlib has no character tables around.

Portability

`wcwidth` has been introduced in the Single UNIX Specification Volume 2 `wcwidth` has been marked as extension in Single UNIX Specification Volume 3

6 Signal Handling ('signal.h')

A *signal* is an event that interrupts the normal flow of control in your program. Your operating environment normally defines the full set of signals available (see 'sys/signal.h'), as well as the default means of dealing with them—typically, either printing an error message and aborting your program, or ignoring the signal.

All systems support at least the following signals:

- SIGABRT Abnormal termination of a program; raised by the <<abort>> function.
- SIGFPE A domain error in arithmetic, such as overflow, or division by zero.
- SIGILL Attempt to execute as a function data that is not executable.
- SIGINT Interrupt; an interactive attention signal.
- SIGSEGV An attempt to access a memory location that is not available.
- SIGTERM A request that your program end execution.

Two functions are available for dealing with asynchronous signals—one to allow your program to send signals to itself (this is called *raising* a signal), and one to specify subroutines (called *handlers* to handle particular signals that you anticipate may occur—whether raised by your own program or the operating environment).

To support these functions, 'signal.h' defines three macros:

- SIG_DFL Used with the `signal` function in place of a pointer to a handler subroutine, to select the operating environment's default handling of a signal.
- SIG_IGN Used with the `signal` function in place of a pointer to a handler, to ignore a particular signal.
- SIG_ERR Returned by the `signal` function in place of a pointer to a handler, to indicate that your request to set up a handler could not be honored for some reason.

'signal.h' also defines an integral type, `sig_atomic_t`. This type is not used in any function declarations; it exists only to allow your signal handlers to declare a static storage location where they may store a signal value. (Static storage is not otherwise reliable from signal handlers.)

6.1 raise—send a signal

Synopsis

```
#include <signal.h>
int raise(int sig);

int _raise_r(void *reent, int sig);
```

Description

Send the signal *sig* (one of the macros from ‘`sys/signal.h`’). This interrupts your program’s normal flow of execution, and allows a signal handler (if you’ve defined one, using `signal`) to take control.

The alternate function `_raise_r` is a reentrant version. The extra argument *reent* is a pointer to a reentrancy structure.

Returns

The result is 0 if *sig* was successfully raised, 1 otherwise. However, the return value (since it depends on the normal flow of execution) may not be visible, unless the signal handler for *sig* terminates with a `return` or unless `SIG_IGN` is in effect for this signal.

Portability

ANSI C requires `raise`, but allows the full set of signal numbers to vary from one implementation to another.

Required OS subroutines: `getpid`, `kill`.

6.2 signal—specify handler subroutine for a signal

Synopsis

```
#include <signal.h>
void ( * signal(int sig, void(*func)(int)) )(int);

void ( * _signal_r(void *reent,
                  int sig, void(*func)(int)) )(int);

int raise (int sig);

int _raise_r (void *reent, int sig);
```

Description

`signal`, `raise` provide a simple signal/raise implementation for embedded targets.

`signal` allows you to request changed treatment for a particular signal `sig`. You can use one of the predefined macros `SIG_DFL` (select system default handling) or `SIG_IGN` (ignore this signal) as the value of `func`; otherwise, `func` is a function pointer that identifies a subroutine in your program as the handler for this signal.

Some of the execution environment for signal handlers is unpredictable; notably, the only library function required to work correctly from within a signal handler is `signal` itself, and only when used to redefine the handler for the current signal value.

Static storage is likewise unreliable for signal handlers, with one exception: if you declare a static storage location as '`volatile sig_atomic_t`', then you may use that location in a signal handler to store signal values.

If your signal handler terminates using `return` (or implicit return), your program's execution continues at the point where it was when the signal was raised (whether by your program itself, or by an external event). Signal handlers can also use functions such as `exit` and `abort` to avoid returning.

`raise` sends the signal `sig` to the executing program. It returns zero if successful, non-zero if unsuccessful.

The alternate functions `_signal_r`, `_raise_r` are the reentrant versions. The extra argument `reent` is a pointer to a reentrancy structure.

Returns

If your request for a signal handler cannot be honored, the result is `SIG_ERR`; a specific error number is also recorded in `errno`.

Otherwise, the result is the previous handler (a function pointer or one of the predefined macros).

Portability

ANSI C requires `raise`, `signal`.

No supporting OS subroutines are required to link with `signal`, but it will not have any useful effects, except for software generated signals, without an operating system that can actually raise exceptions.

7 Time Functions (`'time.h'`)

This chapter groups functions used either for reporting on time (elapsed, current, or compute time) or to perform calculations based on time.

The header file `'time.h'` defines three types. `clock_t` and `time_t` are both used for representations of time particularly suitable for arithmetic. (In this implementation, quantities of type `clock_t` have the highest resolution possible on your machine, and quantities of type `time_t` resolve to seconds.) `size_t` is also defined if necessary for quantities representing sizes.

`'time.h'` also defines the structure `tm` for the traditional representation of Gregorian calendar time as a series of numbers, with the following fields:

<code>tm_sec</code>	Seconds.
<code>tm_min</code>	Minutes.
<code>tm_hour</code>	Hours.
<code>tm_mday</code>	Day.
<code>tm_mon</code>	Month.
<code>tm_year</code>	Year (since 1900).
<code>tm_wday</code>	Day of week: the number of days since Sunday.
<code>tm_yday</code>	Number of days elapsed since last January 1.
<code>tm_isdst</code>	Daylight Savings Time flag: positive means DST in effect, zero means DST not in effect, negative means no information about DST is available.

7.1 `asctime`—format time as string

Synopsis

```
#include <time.h>
char *asctime(const struct tm *clock);
char *asctime_r(const struct tm *clock, char *buf);
```

Description

Format the time value at *clock* into a string of the form

```
Wed Jun 15 11:38:07 1988\n\0
```

The string is generated in a static buffer; each call to `asctime` overwrites the string generated by previous calls.

Returns

A pointer to the string containing a formatted timestamp.

Portability

ANSI C requires `asctime`.

`asctime` requires no supporting OS subroutines.

7.2 clock—cumulative processor time

Synopsis

```
#include <time.h>
clock_t clock(void);
```

Description

Calculates the best available approximation of the cumulative amount of time used by your program since it started. To convert the result into seconds, divide by the macro `CLOCKS_PER_SEC`.

Returns

The amount of processor time used so far by your program, in units defined by the machine-dependent macro `CLOCKS_PER_SEC`. If no measurement is available, the result is `(clock_t)-1`.

Portability

ANSI C requires `clock` and `CLOCKS_PER_SEC`.

Supporting OS subroutine required: `times`.

7.3 `ctime`—convert time to local and format as string

Synopsis

```
#include <time.h>
char *ctime(const time_t *clock);
char *ctime_r(const time_t *clock, char *buf);
```

Description

Convert the time value at *clock* to local time (like `localtime`) and format it into a string of the form

```
Wed Jun 15 11:38:07 1988\n\0
```

(like `asctime`).

Returns

A pointer to the string containing a formatted timestamp.

Portability

ANSI C requires `ctime`.

`ctime` requires no supporting OS subroutines.

7.4 difftime—subtract two times

Synopsis

```
#include <time.h>
double difftime(time_t tim1, time_t tim2);
```

Description

Subtracts the two times in the arguments: '*tim1* - *tim2*'.

Returns

The difference (in seconds) between *tim2* and *tim1*, as a double.

Portability

ANSI C requires `difftime`, and defines its result to be in seconds in all implementations. `difftime` requires no supporting OS subroutines.

7.5 `gmtime`—convert time to UTC traditional form

Synopsis

```
#include <time.h>
struct tm *gmtime(const time_t *clock);
struct tm *gmtime_r(const time_t *clock, struct tm *res);
```

Description

`gmtime` assumes the time at *clock* represents a local time. `gmtime` converts it to UTC (Universal Coordinated Time, also known in some countries as GMT, Greenwich Mean time), then converts the representation from the arithmetic representation to the traditional representation defined by `struct tm`.

`gmtime` constructs the traditional time representation in static storage; each call to `gmtime` or `localtime` will overwrite the information generated by previous calls to either function.

Returns

A pointer to the traditional time representation (`struct tm`).

Portability

ANSI C requires `gmtime`.

`gmtime` requires no supporting OS subroutines.

7.6 localtime—convert time to local representation

Synopsis

```
#include <time.h>
struct tm *localtime(time_t *clock);
struct tm *localtime_r(time_t *clock, struct tm *res);
```

Description

`localtime` converts the time at *clock* into local time, then converts its representation from the arithmetic representation to the traditional representation defined by `struct tm`.

`localtime` constructs the traditional time representation in static storage; each call to `gmtime` or `localtime` will overwrite the information generated by previous calls to either function.

`mktime` is the inverse of `localtime`.

Returns

A pointer to the traditional time representation (`struct tm`).

Portability

ANSI C requires `localtime`.

`localtime` requires no supporting OS subroutines.

7.7 mktime—convert time to arithmetic representation

Synopsis

```
#include <time.h>
time_t mktime(struct tm *timp);
```

Description

`mktime` assumes the time at *timp* is a local time, and converts its representation from the traditional representation defined by `struct tm` into a representation suitable for arithmetic. `localtime` is the inverse of `mktime`.

Returns

If the contents of the structure at *timp* do not form a valid calendar time representation, the result is -1. Otherwise, the result is the time, converted to a `time_t` value.

Portability

ANSI C requires `mktime`.

`mktime` requires no supporting OS subroutines.

7.8 strftime—flexible calendar time formatter

Synopsis

```
#include <time.h>
size_t strftime(char *s, size_t maxsize,
                const char *format, const struct tm *timp);
```

Description

`strftime` converts a `struct tm` representation of the time (at *timp*) into a string, starting at *s* and occupying no more than *maxsize* characters.

You control the format of the output using the string at *format*. **format* can contain two kinds of specifications: text to be copied literally into the formatted string, and time conversion specifications. Time conversion specifications are two-character sequences beginning with '%' (use '%%' to include a percent sign in the output). Each defined conversion specification selects a field of calendar time data from **timp*, and converts it to a string in one of the following ways:

%a	An abbreviation for the day of the week.
%A	The full name for the day of the week.
%b	An abbreviation for the month name.
%B	The full name of the month.
%c	A string representing the complete date and time, in the form Mon Apr 01 13:13:13 1992
%d	The day of the month, formatted with two digits.
%e	The day of the month, formatted with leading space if single digit.
%H	The hour (on a 24-hour clock), formatted with two digits.
%I	The hour (on a 12-hour clock), formatted with two digits.
%j	The count of days in the year, formatted with three digits (from '001' to '366').
%m	The month number, formatted with two digits.
%M	The minute, formatted with two digits.
%p	Either 'AM' or 'PM' as appropriate.
%S	The second, formatted with two digits.
%U	The week number, formatted with two digits (from '00' to '53'; week number 1 is taken as beginning with the first Sunday in a year). See also %W.
%w	A single digit representing the day of the week: Sunday is day 0.
%W	Another version of the week number: like '%U', but counting week 1 as beginning with the first Monday in a year.
o %x	A string representing the complete date, in a format like Mon Apr 01 1992

<code>%X</code>	A string representing the full time of day (hours, minutes, and seconds), in a format like <code>13:13:13</code>
<code>%y</code>	The last two digits of the year.
<code>%Y</code>	The full year, formatted with four digits to include the century.
<code>%Z</code>	The time zone name. If <code>tm_isdst</code> is -1, no output is generated. Otherwise, the time zone name based on the <code>TZ</code> environment variable is used.
<code>%%</code>	A single character, <code>'%'</code> .

Returns

When the formatted time takes up no more than *maxsize* characters, the result is the length of the formatted string. Otherwise, if the formatting operation was abandoned due to lack of room, the result is 0, and the string starting at *s* corresponds to just those parts of **format* that could be completely filled in within the *maxsize* limit.

Portability

ANSI C requires `strftime`, but does not specify the contents of **s* when the formatted string would require more than *maxsize* characters.

`strftime` requires no supporting OS subroutines.

7.9 time—get current calendar time (as single number)

Synopsis

```
#include <time.h>
time_t time(time_t *t);
```

Description

`time` looks up the best available representation of the current time and returns it, encoded as a `time_t`. It stores the same value at `t` unless the argument is `NULL`.

Returns

A `-1` result means the current time is not available; otherwise the result represents the current time.

Portability

ANSI C requires `time`.

Supporting OS subroutine required: Some implementations require `gettimeofday`.

7.10 tzset—set timezone characteristics from TZ environment variable

Synopsis

```
#include <time.h>
void tzset(void);
void _tzset_r (struct _reent *);
```

Description

`tzset` examines the TZ environment variable and sets up the three external variables: `_timezone`, `_daylight`, and `tzname`. The value of `_timezone` shall be the offset from the current time zone to GMT. The value of `_daylight` shall be 0 if there is no daylight savings time for the current time zone, otherwise it will be non-zero. The `tzname` array has two entries: the first is the name of the standard time zone, the second is the name of the daylight-savings time zone.

The TZ environment variable is expected to be in the following POSIX format:

```
stdoffset1[dst[offset2][,start[/time1],end[/time2]]]
```

where: `std` is the name of the standard time-zone (minimum 3 chars) `offset1` is the value to add to local time to arrive at Universal time it has the form: `hh[:mm[:ss]]` `dst` is the name of the alternate (daylight-savings) time-zone (min 3 chars) `offset2` is the value to add to local time to arrive at Universal time it has the same format as the `std` `start` is the day that the alternate time-zone starts `time1` is the optional time that the alternate time-zone starts (this is in local time and defaults to 02:00:00 if not specified) `end` is the day that the alternate time-zone ends `time2` is the time that the alternate time-zone ends (it is in local time and defaults to 02:00:00 if not specified)

Note that there is no white-space padding between fields. Also note that if TZ is null, the default is Universal GMT which has no daylight-savings time. If TZ is empty, the default EST5EDT is used.

The function `_tzset_r` is identical to `tzset` only it is reentrant and is used for applications that use multiple threads.

Returns

There is no return value.

Portability

`tzset` is part of the POSIX standard.

Supporting OS subroutine required: None

8 Locale ('locale.h')

A *locale* is the name for a collection of parameters (affecting collating sequences and formatting conventions) that may be different depending on location or culture. The "C" locale is the only one defined in the ANSI C standard.

This is a minimal implementation, supporting only the required "C" value for locale; strings representing other locales are not honored. (" is also accepted; it represents the default locale for an implementation, here equivalent to "C".

'locale.h' defines the structure `lconv` to collect the information on a locale, with the following fields:

`char *decimal_point`

The decimal point character used to format "ordinary" numbers (all numbers except those referring to amounts of money). "." in the C locale.

`char *thousands_sep`

The character (if any) used to separate groups of digits, when formatting ordinary numbers. "" in the C locale.

`char *grouping`

Specifications for how many digits to group (if any grouping is done at all) when formatting ordinary numbers. The *numeric value* of each character in the string represents the number of digits for the next group, and a value of 0 (that is, the string's trailing NULL) means to continue grouping digits using the last value specified. Use `CHAR_MAX` to indicate that no further grouping is desired. "" in the C locale.

`char *int_curr_symbol`

The international currency symbol (first three characters), if any, and the character used to separate it from numbers. "" in the C locale.

`char *currency_symbol`

The local currency symbol, if any. "" in the C locale.

`char *mon_decimal_point`

The symbol used to delimit fractions in amounts of money. "" in the C locale.

`char *mon_thousands_sep`

Similar to `thousands_sep`, but used for amounts of money. "" in the C locale.

`char *mon_grouping`

Similar to `grouping`, but used for amounts of money. "" in the C locale.

`char *positive_sign`

A string to flag positive amounts of money when formatting. "" in the C locale.

`char *negative_sign`

A string to flag negative amounts of money when formatting. "" in the C locale.

`char int_frac_digits`

The number of digits to display when formatting amounts of money to international conventions. `CHAR_MAX` (the largest number representable as a `char`) in the C locale.

char frac_digits

The number of digits to display when formatting amounts of money to local conventions. `CHAR_MAX` in the C locale.

char p_cs_precedes

1 indicates the local currency symbol is used before a *positive or zero* formatted amount of money; 0 indicates the currency symbol is placed after the formatted number. `CHAR_MAX` in the C locale.

char p_sep_by_space

1 indicates the local currency symbol must be separated from *positive or zero* numbers by a space; 0 indicates that it is immediately adjacent to numbers. `CHAR_MAX` in the C locale.

char n_cs_precedes

1 indicates the local currency symbol is used before a *negative* formatted amount of money; 0 indicates the currency symbol is placed after the formatted number. `CHAR_MAX` in the C locale.

char n_sep_by_space

1 indicates the local currency symbol must be separated from *negative* numbers by a space; 0 indicates that it is immediately adjacent to numbers. `CHAR_MAX` in the C locale.

char p_sign_posn

Controls the position of the *positive* sign for numbers representing money. 0 means parentheses surround the number; 1 means the sign is placed before both the number and the currency symbol; 2 means the sign is placed after both the number and the currency symbol; 3 means the sign is placed just before the currency symbol; and 4 means the sign is placed just after the currency symbol. `CHAR_MAX` in the C locale.

char n_sign_posn

Controls the position of the *negative* sign for numbers representing money, using the same rules as `p_sign_posn`. `CHAR_MAX` in the C locale.

8.1 setlocale, localeconv—select or query locale

Synopsis

```
#include <locale.h>
char *setlocale(int category, const char *locale);
lconv *localeconv(void);

char *_setlocale_r(void *reent,
                  int category, const char *locale);
lconv *_localeconv_r(void *reent);
```

Description

`setlocale` is the facility defined by ANSI C to condition the execution environment for international collating and formatting information; `localeconv` reports on the settings of the current locale.

This is a minimal implementation, supporting only the required "C" value for *locale*; strings representing other locales are not honored unless `MB_CAPABLE` is defined in which case three new extensions are allowed for `LC_CTYPE` or `LC_MESSAGES` only: "C-JIS", "C-EUCJP", "C-SJIS", or "C-ISO-8859-1". (" is also accepted; it represents the default locale for an implementation, here equivalent to "C".)

If you use `NULL` as the *locale* argument, `setlocale` returns a pointer to the string representing the current locale (always "C" in this implementation). The acceptable values for *category* are defined in 'locale.h' as macros beginning with "LC_", but this implementation does not check the values you pass in the *category* argument.

`localeconv` returns a pointer to a structure (also defined in 'locale.h') describing the locale-specific conventions currently in effect.

`_localeconv_r` and `_setlocale_r` are reentrant versions of `localeconv` and `setlocale` respectively. The extra argument *reent* is a pointer to a reentrancy structure.

Returns

`setlocale` returns either a pointer to a string naming the locale currently in effect (always "C" for this implementation, or, if the locale request cannot be honored, `NULL`).

`localeconv` returns a pointer to a structure of type `lconv`, which describes the formatting and collating conventions in effect (in this implementation, always those of the C locale).

Portability

ANSI C requires `setlocale`, but the only locale required across all implementations is the C locale.

No supporting OS subroutines are required.

9 Reentrancy

Reentrancy is a characteristic of library functions which allows multiple processes to use the same address space with assurance that the values stored in those spaces will remain constant between calls. Cygnus's implementation of the library functions ensures that whenever possible, these library functions are reentrant. However, there are some functions that can not be trivially made reentrant. Hooks have been provided to allow you to use these functions in a fully reentrant fashion.

These hooks use the structure `_reent` defined in `'reent.h'`. A variable defined as `'struct _reent'` is called a *reentrancy structure*. All functions which must manipulate global information are available in two versions. The first version has the usual name, and uses a single global instance of the reentrancy structure. The second has a different name, normally formed by prepending `'_'` and appending `'_r'`, and takes a pointer to the particular reentrancy structure to use.

For example, the function `fopen` takes two arguments, *file* and *mode*, and uses the global reentrancy structure. The function `_fopen_r` takes the arguments, *struct_reent*, which is a pointer to an instance of the reentrancy structure, *file* and *mode*.

There are two versions of `'struct _reent'`, a normal one and one for small memory systems, controlled by the `_REENT_SMALL` definition from the (automatically included) `'<sys/config.h>'`.

Each function which uses the global reentrancy structure uses the global variable `_impure_ptr`, which points to a reentrancy structure.

This means that you have two ways to achieve reentrancy. Both require that each thread of execution control initialize a unique global variable of type `'struct _reent'`:

1. Use the reentrant versions of the library functions, after initializing a global reentrancy structure for each process. Use the pointer to this structure as the extra argument for all library functions.
2. Ensure that each thread of execution control has a pointer to its own unique reentrancy structure in the global variable `_impure_ptr`, and call the standard library subroutines.

The following functions are provided in both reentrant and non-reentrant versions.

Equivalent for errno variable:

`_errno_r`

Locale functions:

`_localeconv_r` `_setlocale_r`

Equivalentents for stdio variables:

`_stdin_r` `_stdout_r` `_stderr_r`

Stdio functions:

<code>_fdopen_r</code>	<code>_perror_r</code>	<code>_tempnam_r</code>
<code>_fopen_r</code>	<code>_putchar_r</code>	<code>_tmpnam_r</code>
<code>_getchar_r</code>	<code>_puts_r</code>	<code>_tmpfile_r</code>
<code>_gets_r</code>	<code>_remove_r</code>	<code>_vfprintf_r</code>
<code>_iprintf_r</code>	<code>_rename_r</code>	<code>_vsnprintf_r</code>
<code>_mkstemp_r</code>	<code>_snprintf_r</code>	<code>_vsprintf_r</code>
<code>_mktemp_t</code>	<code>_sprintf_r</code>	

Signal functions:

<code>_init_signal_r</code>	<code>_signal_r</code>
<code>_kill_r</code>	<code>__sigtramp_r</code>
<code>_raise_r</code>	

Stdlib functions:

<code>_calloc_r</code>	<code>_mblen_r</code>	<code>_setenv_r</code>
<code>_dtoa_r</code>	<code>_mbstowcs_r</code>	<code>_srand_r</code>
<code>_free_r</code>	<code>_mbtowc_r</code>	<code>_strtod_r</code>
<code>_getenv_r</code>	<code>_memalign_r</code>	<code>_strtol_r</code>
<code>_mallinfo_r</code>	<code>_mstats_r</code>	<code>_strtoul_r</code>
<code>_malloc_r</code>	<code>_putenv_r</code>	<code>_system_r</code>
<code>_malloc_r</code>	<code>_rand_r</code>	<code>_wcstombs_r</code>
<code>_malloc_stats_r</code>	<code>_realloc_r</code>	<code>_wctomb_r</code>

String functions:

<code>_strdup_r</code>	<code>_strtok_r</code>
------------------------	------------------------

System functions:

<code>_close_r</code>	<code>_link_r</code>	<code>_unlink_r</code>
<code>_execve_r</code>	<code>_lseek_r</code>	<code>_wait_r</code>
<code>_fcntl_r</code>	<code>_open_r</code>	<code>_write_r</code>
<code>_fork_r</code>	<code>_read_r</code>	
<code>_fstat_r</code>	<code>_sbrk_r</code>	
<code>_gettimeofday_r</code>	<code>_stat_r</code>	
<code>_getpid_r</code>	<code>_times_r</code>	

Time function:

<code>_asctime_r</code>

10 Miscellaneous Macros and Functions

This chapter describes miscellaneous routines not covered elsewhere.

10.1 `ffs`—find first bit set in a word

Synopsis

```
int ffs(int word);
```

Description

`ffs` returns the first bit set in a word.

Returns

`ffs` returns 0 if *c* is 0, 1 if *c* is odd, 2 if *c* is a multiple of 2, etc.

Portability

`ffs` is not ANSI C.

No supporting OS subroutines are required.

10.2 unctrl—translate characters to upper case

Synopsis

```
#include <unctrl.h>
char *unctrl(int c);
int unctrlllen(int c);
```

Description

`unctrl` is a macro which returns the printable representation of `c` as a string. `unctrlllen` is a macro which returns the length of the printable representation of `c`.

Returns

`unctrl` returns a string of the printable representation of `c`.

`unctrlllen` returns the length of the string which is the printable representation of `c`.

Portability

`unctrl` and `unctrlllen` are not ANSI C.

No supporting OS subroutines are required.

11 System Calls

The C subroutine library depends on a handful of subroutine calls for operating system services. If you use the C library on a system that complies with the POSIX.1 standard (also known as IEEE 1003.1), most of these subroutines are supplied with your operating system.

If some of these subroutines are not provided with your system—in the extreme case, if you are developing software for a “bare board” system, without an OS—you will at least need to provide do-nothing stubs (or subroutines with minimal functionality) to allow your programs to link with the subroutines in `libc.a`.

11.1 Definitions for OS interface

This is the complete set of system definitions (primarily subroutines) required; the examples shown implement the minimal functionality required to allow `libc` to link, and fail gracefully where OS services are not available.

Graceful failure is permitted by returning an error code. A minor complication arises here: the C library must be compatible with development environments that supply fully functional versions of these subroutines. Such environments usually return error codes in a global `errno`. However, the Cygnus C library provides a *macro* definition for `errno` in the header file ‘`errno.h`’, as part of its support for reentrant routines (see Chapter 9 [Reentrancy], page 205).

The bridge between these two interpretations of `errno` is straightforward: the C library routines with OS interface calls capture the `errno` values returned globally, and record them in the appropriate field of the reentrancy structure (so that you can query them using the `errno` macro from ‘`errno.h`’).

This mechanism becomes visible when you write stub routines for OS interfaces. You must include ‘`errno.h`’, then disable the macro, like this:

```
#include <errno.h>
#undef errno
extern int errno;
```

The examples in this chapter include this treatment of `errno`.

_exit Exit a program without cleaning up files. If your system doesn’t provide this, it is best to avoid linking with subroutines that require it (`exit`, `system`).

close Close a file. Minimal implementation:

```
int close(int file){
    return -1;
}
```

environ A pointer to a list of environment variables and their values. For a minimal environment, this empty list is adequate:

```
char *__env[1] = { 0 };
char **environ = __env;
```

execve Transfer control to a new process. Minimal implementation (for a system without processes):

```

#include <errno.h>
#undef errno
extern int errno;
int execve(char *name, char **argv, char **env){
    errno=ENOMEM;
    return -1;
}

```

fork Create a new process. Minimal implementation (for a system without processes):

```

#include <errno.h>
#undef errno
extern int errno;
int fork() {
    errno=EAGAIN;
    return -1;
}

```

fstat Status of an open file. For consistency with other minimal implementations in these examples, all files are regarded as character special devices. The 'sys/stat.h' header file required is distributed in the 'include' subdirectory for this C library.

```

#include <sys/stat.h>
int fstat(int file, struct stat *st) {
    st->st_mode = S_IFCHR;
    return 0;
}

```

getpid Process-ID; this is sometimes used to generate strings unlikely to conflict with other processes. Minimal implementation, for a system without processes:

```

int getpid() {
    return 1;
}

```

isatty Query whether output stream is a terminal. For consistency with the other minimal implementations, which only support output to `stdout`, this minimal implementation is suggested:

```

int isatty(int file){
    return 1;
}

```

kill Send a signal. Minimal implementation:

```

#include <errno.h>
#undef errno
extern int errno;
int kill(int pid, int sig){
    errno=EINVAL;
    return(-1);
}

```

link Establish a new name for an existing file. Minimal implementation:

```

#include <errno.h>
#undef errno
extern int errno;
int link(char *old, char *new){
    errno=EMLINK;
    return -1;
}

```

lseek Set position in a file. Minimal implementation:

```

int lseek(int file, int ptr, int dir){
    return 0;
}

```

open Open a file. Minimal implementation:

```

int open(const char *name, int flags, int mode){
    return -1;
}

```

read Read from a file. Minimal implementation:

```

int read(int file, char *ptr, int len){
    return 0;
}

```

sbrk Increase program data space. As `malloc` and related functions depend on this, it is useful to have a working implementation. The following suffices for a standalone system; it exploits the symbol `end` automatically defined by the GNU linker.

```

caddr_t sbrk(int incr){
    extern char end; /* Defined by the linker */
    static char *heap_end;
    char *prev_heap_end;

    if (heap_end == 0) {
        heap_end = &end;
    }
    prev_heap_end = heap_end;
    if (heap_end + incr > stack_ptr)
    {
        _write (1, "Heap and stack collision\n", 25);
        abort ();
    }

    heap_end += incr;
    return (caddr_t) prev_heap_end;
}

```

stat Status of a file (by name). Minimal implementation:

```

int stat(char *file, struct stat *st) {
    st->st_mode = S_IFCHR;
}

```

```

        return 0;
    }

```

times Timing information for current process. Minimal implementation:

```

    int times(struct tms *buf){
        return -1;
    }

```

unlink Remove a file's directory entry. Minimal implementation:

```

#include <errno.h>
#undef errno
extern int errno;
int unlink(char *name){
    errno=ENOENT;
    return -1;
}

```

wait Wait for a child process. Minimal implementation:

```

#include <errno.h>
#undef errno
extern int errno;
int wait(int *status) {
    errno=ECHILD;
    return -1;
}

```

write Write a character to a file. 'libc' subroutines will use this system routine for output to all files, *including stdout*—so if you need to generate any output, for example to a serial port for debugging, you should make your minimal **write** capable of doing this. The following minimal implementation is an incomplete example; it relies on a **writchar** subroutine (not shown; typically, you must write this in assembler from examples provided by your hardware manufacturer) to actually perform the output.

```

    int write(int file, char *ptr, int len){
        int todo;

        for (todo = 0; todo < len; todo++) {
            writchar(*ptr++);
        }
        return len;
    }

```

11.2 Reentrant covers for OS subroutines

Since the system subroutines are used by other library routines that require reentrancy, 'libc.a' provides cover routines (for example, the reentrant version of `fork` is `_fork_r`). These cover routines are consistent with the other reentrant subroutines in this library, and achieve reentrancy by using a reserved global data block (see Chapter 9 [Reentrancy], page 205).

- `_open_r` A reentrant version of `open`. It takes a pointer to the global data block, which holds `errno`.
`int _open_r(void *reent, const char *file, int flags, int mode);`
- `_close_r` A reentrant version of `close`. It takes a pointer to the global data block, which holds `errno`.
`int _close_r(void *reent, int fd);`
- `_lseek_r` A reentrant version of `lseek`. It takes a pointer to the global data block, which holds `errno`.
`off_t _lseek_r(void *reent, int fd, off_t pos, int whence);`
- `_read_r` A reentrant version of `read`. It takes a pointer to the global data block, which holds `errno`.
`long _read_r(void *reent, int fd, void *buf, size_t cnt);`
- `_write_r` A reentrant version of `write`. It takes a pointer to the global data block, which holds `errno`.
`long _write_r(void *reent, int fd, const void *buf, size_t cnt);`
- `_fork_r` A reentrant version of `fork`. It takes a pointer to the global data block, which holds `errno`.
`int _fork_r(void *reent);`
- `_wait_r` A reentrant version of `wait`. It takes a pointer to the global data block, which holds `errno`.
`int _wait_r(void *reent, int *status);`
- `_stat_r` A reentrant version of `stat`. It takes a pointer to the global data block, which holds `errno`.
`int _stat_r(void *reent, const char *file, struct stat *pstat);`
- `_fstat_r` A reentrant version of `fstat`. It takes a pointer to the global data block, which holds `errno`.
`int _fstat_r(void *reent, int fd, struct stat *pstat);`
- `_link_r` A reentrant version of `link`. It takes a pointer to the global data block, which holds `errno`.

```
int _link_r(void *reent,  
            const char *old, const char *new);
```

`_unlink_r`

A reentrant version of `unlink`. It takes a pointer to the global data block, which holds `errno`.

```
int _unlink_r(void *reent, const char *file);
```

`_sbrk_r`

A reentrant version of `sbrk`. It takes a pointer to the global data block, which holds `errno`.

```
char *_sbrk_r(void *reent, size_t incr);
```

12 Variable Argument Lists

The `printf` family of functions is defined to accept a variable number of arguments, rather than a fixed argument list. You can define your own functions with a variable argument list, by using macro definitions from either `'stdarg.h'` (for compatibility with ANSI C) or from `'varargs.h'` (for compatibility with a popular convention prior to ANSI C).

12.1 ANSI-standard macros, `'stdarg.h'`

In ANSI C, a function has a variable number of arguments when its parameter list ends in an ellipsis (...). The parameter list must also include at least one explicitly named argument; that argument is used to initialize the variable list data structure.

ANSI C defines three macros (`va_start`, `va_arg`, and `va_end`) to operate on variable argument lists. `'stdarg.h'` also defines a special type to represent variable argument lists: this type is called `va_list`.

12.1.1 Initialize variable argument list

Synopsis

```
#include <stdarg.h>
void va_start(va_list ap, rightmost);
```

Description

Use `va_start` to initialize the variable argument list `ap`, so that `va_arg` can extract values from it. `rightmost` is the name of the last explicit argument in the parameter list (the argument immediately preceding the ellipsis ‘...’ that flags variable arguments in an ANSI C function header). You can only use `va_start` in a function declared using this ellipsis notation (not, for example, in one of its subfunctions).

Returns

`va_start` does not return a result.

Portability

ANSI C requires `va_start`.

12.1.2 Extract a value from argument list

Synopsis

```
#include <stdarg.h>
type va_arg(va_list ap, type);
```

Description

`va_arg` returns the next unprocessed value from a variable argument list *ap* (which you must previously create with *va_start*). Specify the type for the value as the second parameter to the macro, *type*.

You may pass a `va_list` object *ap* to a subfunction, and use `va_arg` from the subfunction rather than from the function actually declared with an ellipsis in the header; however, in that case you may *only* use `va_arg` from the subfunction. ANSI C does not permit extracting successive values from a single variable-argument list from different levels of the calling stack.

There is no mechanism for testing whether there is actually a next argument available; you might instead pass an argument count (or some other data that implies an argument count) as one of the fixed arguments in your function call.

Returns

`va_arg` returns the next argument, an object of type *type*.

Portability

ANSI C requires `va_arg`.

12.1.3 Abandon a variable argument list

Synopsis

```
#include <stdarg.h>
void va_end(va_list ap);
```

Description

Use `va_end` to declare that your program will not use the variable argument list `ap` any further.

Returns

`va_end` does not return a result.

Portability

ANSI C requires `va_end`.

12.2 Traditional macros, ‘`varargs.h`’

If your C compiler predates ANSI C, you may still be able to use variable argument lists using the macros from the ‘`varargs.h`’ header file. These macros resemble their ANSI counterparts, but have important differences in usage. In particular, since traditional C has no declaration mechanism for variable argument lists, two additional macros are provided simply for the purpose of defining functions with variable argument lists.

As with ‘`stdarg.h`’, the type `va_list` is used to hold a data structure representing a variable argument list.

12.2.1 Declare variable arguments

Synopsis

```
#include <varargs.h>
function(va_alist)
va_dcl
```

Description

To use the ‘`varargs.h`’ version of variable argument lists, you must declare your function with a call to the macro `va_alist` as its argument list, and use `va_dcl` as the declaration. *Do not use a semicolon after `va_dcl`.*

Returns

These macros cannot be used in a context where a return is syntactically possible.

Portability

`va_alist` and `va_dcl` were the most widespread method of declaring variable argument lists prior to ANSI C.

12.2.2 Initialize variable argument list

Synopsis

```
#include <varargs.h>
va_list ap;
va_start(ap);
```

Description

With the ‘`varargs.h`’ macros, use `va_start` to initialize a data structure `ap` to permit manipulating a variable argument list. `ap` must have the type `va_alist`.

Returns

`va_start` does not return a result.

Portability

`va_start` is also defined as a macro in ANSI C, but the definitions are incompatible; the ANSI version has another parameter besides `ap`.

12.2.3 Extract a value from argument list

Synopsis

```
#include <varargs.h>
type va_arg(va_list ap, type);
```

Description

`va_arg` returns the next unprocessed value from a variable argument list *ap* (which you must previously create with `va_start`). Specify the type for the value as the second parameter to the macro, *type*.

Returns

`va_arg` returns the next argument, an object of type *type*.

Portability

The `va_arg` defined in ‘`varargs.h`’ has the same syntax and usage as the ANSI C version from ‘`stdarg.h`’.

12.2.4 Abandon a variable argument list

Synopsis

```
#include <varargs.h>
va_end(va_list ap);
```

Description

Use `va_end` to declare that your program will not use the variable argument list `ap` any further.

Returns

`va_end` does not return a result.

Portability

The `va_end` defined in `'varargs.h'` has the same syntax and usage as the ANSI C version from `'stdarg.h'`.

Index

-	
__env_lock	14
__env_unlock	14
__malloc_lock	24
__malloc_unlock	24
_asctime_r	190
_atoi_r	7
_atol_r	7
_atoll_r	8
_calloc_r	9
_close_r	215
_exit	211
_fdopen_r	83
_fgetpos_r	78
_fopen_r	81
_fork_r	215
_free_r	21
_freopen_r	87
_fseek_r	88
_fseeko_r	88
_fsetpos_r	89
_fstat_r	215
_ftell_r	90
_ftello_r	90
_getchar_r	93
_gets_r	94
_impure_ptr	205
_link_r	215
_localeconv_r	203
_lseek_r	215
_mallinfo_r	23
_malloc_r	21
_malloc_stats_r	23
_malloc_usable_size_r	21
_mallopt_r	23
_memalign_r	21
_mkstemp_r	97
_mktemp_r	97
_open_r	215
_perror_r	98
_putchar_r	100
_puts_r	101
_raise_r	186, 187
_read_r	215
_realloc_r	21
_reent	205
_rename_r	104
_rewind_r	105
_sbrk_r	216
_setlocale_r	203
_signal_r	187
_stat_r	215
_strtod_r	31
_strtol_r	32
_strtoul_r	34
_system_r	36
_tempnam_r	119
_tmpfile_r	118
_tmpnam_r	119
_tolower	52
_toupper	53
_unlink_r	216
_wait_r	215
_write_r	215
A	
abort	2
abs	3
asctime	190
asprintf	109
assert	4
atexit	5
atof	6
atoff	6
atoi	7
atol	7
atoll	8
B	
bcmp	122
bzero	124
C	
calloc	9
clearerr	72
clock	191
close	211
ctime	192
D	
difftime	193
div	10
drand48	29
E	
ecvt	11
ecvtbuf	13
environ	16, 211
erand48	29
errno global vs macro	211
execve	211
exit	15
extra argument, reentrant fns	205

F

fclose	73
fcvt	11
fcvtbuf	13
fdopen	83
feof	74
ferror	75
fflush	76
ffs	208
fgetc	77
fgetpos	78
fgets	79
fiprintf	80
fopen	81
fork	212
fprintf	109
fputc	84
fputs	85
fread	86
free	21
freopen	87
fscanf	113
fseek	88
fseeko	88
fsetpos	89
fstat	212
ftell	90
ftello	90
fwrite	91

G

gcvt	12
gcvtf	12
getc	92
getchar	93
getenv	16
getpid	212
gets	94
getw	95
global reentrancy structure	205
gmtime	194

I

index	125
iprintf	96
isalnum	40
isalpha	41
isascii	42
isatty	212
iscntrl	43
isdigit	44
isgraph	46
islower	45
isprint	46
ispunct	47
isspace	48

isupper	49
iswalnum	54
iswalph	55
iswcntrl	56
iswctype	65
iswdigit	57
iswgraph	58
iswlower	59
iswprint	60
iswpunct	61
iswspace	62
iswupper	63
iswxdigit	64
isxdigit	50

J

jrand48	29
---------	----

K

kill	212
------	-----

L

labs	17
lcong48	29
ldiv	18
link	212
linking the C library	211
list of reentrant functions	205
llabs	19
lldiv	20
localeconv	203
localtime	195
lrand48	29
lseek	213

M

mallinfo	23
malloc	21
malloc_stats	23
malloc_usable_size	21
mallopt	23
mblen	25
mbstowcs	26
mbtowc	27
memalign	21
memchr	127
memcmp	128
memmove	130
memset	132
mkstemp	97
mktemp	97
mkttime	196
mrnd48	29

N

nrnd48 29

O

open 213
OS interface subroutines 211

P

perror 98
printf 109
putc 99
putchar 100
puts 101
putw 102

R

raise 186, 187
rand 28
rand_r 28
rand48 29
read 213
realloc 21
reent.h 205
reentrancy 205
reentrancy structure 205
reentrant function list 205
remove 103
rename 104
rewind 105
rindex 133

S

sbrk 213
scanf 113
seed48 29
setbuf 106
setlocale 203
setvbuf 107
signal 187
siprintf 108
snprintf 109
sprintf 109
srand 28
srand48 29
sscanf 113
stat 213
strcasecmp 134
strcat 135
strchr 136
strcmp 137
strcoll 138
strcpy 139
strcspn 140
strerror 141

strftime 197
strlen 145
strlwr 146
strncasecmp 147
strncat 148
strncmp 149
strncpy 150
strpbrk 151
strrchr 152
strsep 155
strspn 153
strstr 154
strtod 31
strtof 31
strtok 155
strtok_r 155
strtol 32
strtoul 34
strupr 156
strxfrm 157
stubs 211
subroutines for OS interface 211
system 36

T

tempnam 119
time 199
times 214
tmpfile 118
tmpnam 119
toascii 51
tolower 52
toupper 53
towctrans 69
towlower 67
towupper 68
tzset 200

U

unctrl 209
unctrlrlen 209
unlink 214

V

va_alist 221
va_arg 219, 223
va_dcl 221
va_end 220, 224
va_start 218, 222
vfprintf 120
vprintf 120
vsnprintf 120
vsprintf 120

W

<code>wait</code>	214	<code>wcswidth</code>	182
<code>wcscat</code>	165	<code>wctomb</code>	38
<code>wscoll</code>	168	<code>wctrans</code>	70
<code>wcsnlen</code>	177	<code>wctype</code>	66
<code>wcstombs</code>	37	<code>wcwidth</code>	183
		<code>write</code>	214

The body of this manual is set in
cmr10 at 10.95pt,
with headings in **cmb10 at 10.95pt**
and examples in cmtt10 at 10.95pt.
cmti10 at 10.95pt and
cmsl10 at 10.95pt
are used for emphasis.

Table of Contents

1	Standard Utility Functions ('stdlib.h')	1
1.1	abort—abnormal termination of a program	2
1.2	abs—integer absolute value (magnitude)	3
1.3	assert—Macro for Debugging Diagnostics	4
1.4	atexit—request execution of functions at program exit	5
1.5	atof, atoff—string to double or float	6
1.6	atoi, atol—string to integer	7
1.7	atoll—convert a string to a long long integer	8
1.8	calloc—allocate space for arrays	9
1.9	div—divide two integers	10
1.10	ecvt, ecvtf, fcvt, fcvtf—double or float to string	11
1.11	gvcvt, gcvtf—format double or float as string	12
1.12	ecvtbuf, fcvtbuf—double or float to string	13
1.13	__env_lock, __env_unlock—lock environ variable	14
1.14	exit—end program execution	15
1.15	getenv—look up environment variable	16
1.16	labs—long integer absolute value	17
1.17	ldiv—divide two long integers	18
1.18	llabs—compute the absolute value of a long long integer	19
1.19	lldiv—divide two long long integers	20
1.20	malloc, realloc, free—manage memory	21
1.21	mallinfo, malloc_stats, mallopt—malloc support	23
1.22	__malloc_lock, __malloc_unlock—lock malloc pool	24
1.23	mblen—minimal multibyte length function	25
1.24	mbstowcs—minimal multibyte string to wide char converter	26
1.25	mbtowc—minimal multibyte to wide char converter	27
1.26	rand, srand—pseudo-random numbers	28
1.27	rand48, drand48, erand48, lrand48, nrand48, mrand48, jrand48, srand48, seed48, lcong48—pseudo random number generators and initialization routines	29
1.28	strtod, strtodf—string to double or float	31
1.29	strtol—string to long	32
1.30	strtoul—string to unsigned long	34
1.31	system—execute command string	36
1.32	wcstombs—minimal wide char string to multibyte string converter	37
1.33	wctomb—minimal wide char to multibyte converter	38

2	Character Type Macros and Functions	
	(‘ctype.h’)	39
2.1	isalnum—alphanumeric character predicate	40
2.2	isalpha—alphabetic character predicate	41
2.3	isascii—ASCII character predicate	42
2.4	iscntrl—control character predicate	43
2.5	isdigit—decimal digit predicate	44
2.6	islower—lower-case character predicate	45
2.7	isprint, isgraph—printable character predicates	46
2.8	ispunct—punctuation character predicate	47
2.9	isspace—whitespace character predicate	48
2.10	isupper—uppercase character predicate	49
2.11	isxdigit—hexadecimal digit predicate	50
2.12	toascii—force integers to ASCII range	51
2.13	tolower—translate characters to lower case	52
2.14	toupper—translate characters to upper case	53
2.15	iswalnum—alpha-numeric wide-character test	54
2.16	iswalpha—alphabetic wide-character test	55
2.17	iswcntrl—wide-character cntrl test	56
2.18	iswdigit—decimal digit wide-character test	57
2.19	iswgraph—graphic wide-character test	58
2.20	iswlower—lower-case wide-character test	59
2.21	iswprint—printable wide-character test	60
2.22	iswpunct—punctuation wide-character test	61
2.23	iswspace—wide-character space test	62
2.24	iswupper—upper-case wide-character test	63
2.25	iswxdigit—hexadecimal digit wide-character test	64
2.26	iswctype—extensible wide-character test	65
2.27	wctype—get wide-character classification type	66
2.28	tolower—translate wide-characters to lower case	67
2.29	toupper—translate wide-characters to upper case	68
2.30	towctrans—extensible wide-character case mapping	69
2.31	wctrans—get wide-character translation type	70
3	Input and Output (‘stdio.h’)	71
3.1	clearerr—clear file or stream error indicator	72
3.2	fclose—close a file	73
3.3	feof—test for end of file	74
3.4	ferror—test whether read/write error has occurred	75
3.5	fflush—flush buffered file output	76
3.6	fgetc—get a character from a file or stream	77
3.7	fgetpos—record position in a stream or file	78
3.8	fgets—get character string from a file or stream	79
3.9	fiprintf—format output to file (integer only)	80
3.10	fopen—open a file	81
3.11	fdopen—turn open file into a stream	83
3.12	fputc—write a character on a stream or file	84
3.13	fputs—write a character string in a file or stream	85

3.14	<code>fread</code> —read array elements from a file.....	86
3.15	<code>freopen</code> —open a file using an existing file descriptor.....	87
3.16	<code>fseek</code> , <code>fseeko</code> —set file position.....	88
3.17	<code>fsetpos</code> —restore position of a stream or file.....	89
3.18	<code>ftell</code> , <code>ftello</code> —return position in a stream or file.....	90
3.19	<code>fwrite</code> —write array elements.....	91
3.20	<code>getc</code> —read a character (macro).....	92
3.21	<code>getchar</code> —read a character (macro).....	93
3.22	<code>gets</code> —get character string (obsolete, use <code>fgets</code> instead)..	94
3.23	<code>getw</code> —read a word (int).....	95
3.24	<code>iprintf</code> —write formatted output (integer only).....	96
3.25	<code>mktemp</code> , <code>mkstemp</code> —generate unused file name.....	97
3.26	<code>perror</code> —print an error message on standard error.....	98
3.27	<code>putc</code> —write a character (macro).....	99
3.28	<code>putchar</code> —write a character (macro).....	100
3.29	<code>puts</code> —write a character string.....	101
3.30	<code>putw</code> —write a word (int).....	102
3.31	<code>remove</code> —delete a file’s name.....	103
3.32	<code>rename</code> —rename a file.....	104
3.33	<code>rewind</code> —reinitialize a file or stream.....	105
3.34	<code>setbuf</code> —specify full buffering for a file or stream.....	106
3.35	<code>setvbuf</code> —specify file or stream buffering.....	107
3.36	<code>siprintf</code> —write formatted output (integer only).....	108
3.37	<code>printf</code> , <code>fprintf</code> , <code>asprintf</code> , <code>sprintf</code> , <code>snprintf</code> —format output.....	109
3.38	<code>scanf</code> , <code>fscanf</code> , <code>sscanf</code> —scan and format input.....	113
3.39	<code>tmpfile</code> —create a temporary file.....	118
3.40	<code>tmpnam</code> , <code>tempnam</code> —name for a temporary file.....	119
3.41	<code>vprintf</code> , <code>vfprintf</code> , <code>vsprintf</code> —format argument list...	120
4	Strings and Memory (‘string.h’).....	121
4.1	<code>bcmp</code> —compare two memory areas.....	122
4.2	<code>bcopy</code> —copy memory regions.....	123
4.3	<code>bzero</code> —initialize memory to zero.....	124
4.4	<code>index</code> —search for character in string.....	125
4.5	<code>memccpy</code> —copy memory regions with end-token check....	126
4.6	<code>memchr</code> —find character in memory.....	127
4.7	<code>memcmp</code> —compare two memory areas.....	128
4.8	<code>memcpy</code> —copy memory regions.....	129
4.9	<code>memmove</code> —move possibly overlapping memory.....	130
4.10	<code>mempcpy</code> —copy memory regions and return end pointer..	131
4.11	<code>memset</code> —set an area of memory.....	132
4.12	<code>rindex</code> —reverse search for character in string.....	133
4.13	<code>strcasecmp</code> —case insensitive character string compare..	134
4.14	<code>strcat</code> —concatenate strings.....	135
4.15	<code>strchr</code> —search for character in string.....	136
4.16	<code>strcmp</code> —character string compare.....	137
4.17	<code>strcoll</code> —locale specific character string compare.....	138

4.18	strcpy —copy string.....	139
4.19	strcspn —count chars not in string.....	140
4.20	strerror —convert error number to string.....	141
4.21	strlen —character string length.....	145
4.22	strlwr —force string to lower case.....	146
4.23	strncasecmp —case insensitive character string compare	147
4.24	strncat —concatenate strings.....	148
4.25	strncmp —character string compare.....	149
4.26	strncpy —counted copy string.....	150
4.27	strpbrk —find chars in string.....	151
4.28	strrchr —reverse search for character in string.....	152
4.29	strspn —find initial match.....	153
4.30	strstr —find string segment.....	154
4.31	strtok, strtok_r, strsep —get next token from a string	155
4.32	strupr —force string to uppercase.....	156
4.33	strxfrm —transform string.....	157
4.34	swab —swap adjacent bytes.....	158
5	Wide Character Strings ('wchar.h')	159
5.1	wmemchr —find a wide-character in memory.....	160
5.2	wmemcmp —compare wide-characters in memory.....	161
5.3	wmemcpy —copy wide-characters in memory.....	162
5.4	wmemmove —wmemmove - copy wide-characters in memory with overlapping areas.....	163
5.5	wmemset —set wide-characters in memory.....	164
5.6	wscat —concatenate two wide-character strings.....	165
5.7	wcschr —wide-character string scanning operation.....	166
5.8	wscmp —compare two wide-character strings.....	167
5.9	wscoll —locale specific wide-character string compare... ..	168
5.10	wscpy —copy a wide-character string.....	169
5.11	wcscspn —get length of a complementary wide substring	170
5.12	wcslcat —concatenate wide-character strings to specified length.....	171
5.13	wcslcpy —copy a wide-character string to specified length	172
5.14	wcslen —get wide-character string length.....	173
5.15	wcsncat —concatenate part of two wide-character strings	174
5.16	wcsncmp —compare part of two wide-character strings... ..	175
5.17	wcsncpy —copy part of a wide-character string.....	176
5.18	wcsnlen —get fixed-size wide character string length....	177
5.19	wcspbrk —scan wide-character string for a wide-character code.....	178
5.20	wcsrchr —wide-character string scanning operation.....	179
5.21	wcsspn —get length of a wide substring.....	180

5.22	<code>wcsstr</code> —find a wide-character substring	181
5.23	<code>wcswidth</code> —number of column positions of a wide-character string	182
5.24	<code>wcwidth</code> —number of column positions of a wide-character code	183
6	Signal Handling (<code>'signal.h'</code>)	185
6.1	<code>raise</code> —send a signal	186
6.2	<code>signal</code> —specify handler subroutine for a signal	187
7	Time Functions (<code>'time.h'</code>)	189
7.1	<code>asctime</code> —format time as string	190
7.2	<code>clock</code> —cumulative processor time	191
7.3	<code>ctime</code> —convert time to local and format as string	192
7.4	<code>difftime</code> —subtract two times	193
7.5	<code>gmtime</code> —convert time to UTC traditional form	194
7.6	<code>localtime</code> —convert time to local representation	195
7.7	<code>mktime</code> —convert time to arithmetic representation	196
7.8	<code>strftime</code> —flexible calendar time formatter	197
7.9	<code>time</code> —get current calendar time (as single number)	199
7.10	<code>tzset</code> —set timezone characteristics from TZ environment variable	200
8	Locale (<code>'locale.h'</code>)	201
8.1	<code>setlocale</code> , <code>localeconv</code> —select or query locale	203
9	Reentrancy	205
10	Miscellaneous Macros and Functions	207
10.1	<code>ffs</code> —find first bit set in a word	208
10.2	<code>unctrl</code> —translate characters to upper case	209
11	System Calls	211
11.1	Definitions for OS interface	211
11.2	Reentrant covers for OS subroutines	215
12	Variable Argument Lists	217
12.1	ANSI-standard macros, <code>'stdarg.h'</code>	217
12.1.1	Initialize variable argument list	218
12.1.2	Extract a value from argument list	219
12.1.3	Abandon a variable argument list	220
12.2	Traditional macros, <code>'varargs.h'</code>	220
12.2.1	Declare variable arguments	221
12.2.2	Initialize variable argument list	222
12.2.3	Extract a value from argument list	223
12.2.4	Abandon a variable argument list	224

Index **225**